

# CAPELLA LED EDGE BOX RING VD 1950LM 840 IP54 PIR WHITE (21W) 340MM

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	940446
Ingress protection:	IP54
Impact resistance:	IK07
Nominal power [W]:	21
Luminous flux [lm]*:	1950
Colour temperature [K]:	4000
SDCM:	≤ 5
Energy efficiency class:	F
Material of the body:	ABS
Ring material:	ABS

## CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.


# CAPELLA LED EDGE BOX RING VD 1950LM 840 IP54 PIR WHITE (21W) 340MM

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Working temperature [°C]:	from -20 to +35
Nominal power [W]:	21	Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Rated power of the luminaire [W]:	24	Dimensions of single box [mm]:	342/342/122
Supply voltage [V]:	220-240	Net weight [kg]:	0.900
Luminous flux [lm]:	1950	Warranty [years]:	5
Luminous efficacy [lm/W]:	78	Flicker procent:	100
Energy efficiency class:	F	Index:	940446
Electrical protection class:	II	Category type:	bulkheads
Colour temperature [K]:	4000	Category of application:	educational institutions
Colour rendering index:	>80	Rated power rating 30min [W]:	23.70
SDCM:	≤ 5	Luminous flux of the luminaire 0 min [lm]*:	1914
Power factor:	0.98	AC voltage range [V]:	220 - 240
Beam angle [°]:	120	ITHD [%]:	14
Surge protection [kV]:	2	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	EDGE/BOX Colour:	white
Diffuser type:	OPAL	EAN:	CAPELLA LED EDGE BOX RI
Material of the body:	ABS	Frequency [Hz]:	50 - 60
Colour of the body:	white	PIR:	yes
Ring material:	ABS	PKP Certificate:	940446
Ring colour:	white	Dusk sensor:	yes
Dimensions (H/W/T/S) [mm]:	340/105	LED lifespan L70B50 [h]:	12000
Mounting dimensions [mm]:	160	LED lifespan L80B20 [h]:	78000
Impact resistance:	IK07	LED lifespan L90B10 [h]:	40000
Ingress protection:	IP54	Warranty [years]:	5
Mounting version:	surface	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



# CAPELLA LED EDGE BOX RING VD 1950LM 840 IP54 PIR WHITE (21W) 340MM

DETAILED CARD

## TECHNICAL DETAILS



CAPELLA LED EDGE

Card creation date: 23 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 156/2020



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl