

# DIONE LED PLUS ASYMMETRIC DP 2300-3200LM 840 IP65 I KL. AW 3H AT OPAL WHITE MULTI LED

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK10
<b>Nominal power [W] - range:</b>	21/27/32
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux of the luminaire [lm] - range:</b>	2300/2800/3200
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Ring material:</b>	ABS
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

The MULTI luminaire version allows individual configuration: thanks to the built-in micoswitch, it is possible to choose one of three settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.


# DIONE LED PLUS ASYMMETRIC DP 2300-3200LM 840 IP65 I KL. AW 3H AT OPAL WHITE MULTI LED

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	940194	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP65
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from 0 to +25
Energy efficiency class:	E	Dimensions of single box [mm]:	340/340/115
Electrical protection class:	I	Net weight [kg]:	1.250
Nominal power [W] - range:	21/27/32	Warranty [years]:	5
Colour temperature [K]:	4000	Permeability factor of the diffuser:	0.73
Luminous flux of the luminaire [lm] - range:	2300/2800/3200	Category type:	bulkheads
Colour rendering index:	>80	Category of application:	commercial facilities, educational institutions
SDCM:	≤ 3	AC voltage range [V]:	198-264
Power factor:	0.93	LED lifespan L70B50 [h]:	115000
Beam angle [°]:	120	LED lifespan L80B20 [h]:	75000
Surge protection [kV]:	1	LED lifespan L90B10 [h]:	33000
Diffuser material:	PC	Luminous efficacy [lm/W]:	97
Diffuser type:	OPAL	Emergency lighting [h]:	3
Diffuser colour:	white	Autotest:	yes
Material of the body:	ABS	Light distribution type:	asymmetric
Colour of the body:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ring material:	ABS	Manual:	<a href="#">Download PDF</a>
Ring colour:	white	CE certificate:	<a href="#">381/2023</a>
Dimensions (H/W/T/S) [mm]:	340/115	PZH certificate:	<a href="#">B-BK-60212-0619/20</a>
Mounting dimensions [mm]:	140		

## LIGHT CURVES



# DIONE LED PLUS ASYMMETRIC DP 2300-3200LM 840 IP65 I KL. AW 3H AT OPAL WHITE MULTI LED

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant (120DL118)

Card creation date: 26 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 381/2023