

DIONE LED PLUS ASYMMETRIC DP 2150LM 830 IP65 I KL. RCR AW 3H AT OPAL WHITE 21W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	940200
Nominal power [W]:	21
Luminous flux [lm]*:	2150
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS ASYMMETRIC DP 2150LM 830 IP65 I KL. RCR AW 3H AT OPAL WHITE 21W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	21	Mounting version:	surface
Index:	940200	Working temperature [°C]:	from 0 to +25
Colour temperature [K]:	3000	Motion sensor:	yes
Luminous flux [lm]:	2150	Emergency lighting [h]:	3
Light source:	LED module	Dimensions of single box [mm]:	340/340/115
Diffuser type:	OPAL	Net weight [kg]:	1.300
Rated power of the luminaire [W]:	22	Warranty [years]:	2 / 0.5 (bateria)
Supply voltage [V]:	220-240	Permeability factor of the diffuser:	0.73
Frequency [Hz]:	50 - 60	Category type:	bulkheads
Luminous efficacy [lm/W]:	98	Category of application:	commercial facilities, educational institutions
Energy efficiency class:	E	Version:	DP painted diffuser
Electrical protection class:	I	AC voltage range [V]:	198-264
Colour rendering index:	>80	DC voltage range [V]:	176-280
SDCM:	≤ 3	LED lifespan L70B50 [h]:	115000
Power factor:	0.94	LED lifespan L80B20 [h]:	75000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	33000
Surge protection [kV]:	1	Light distribution type:	asymmetric
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser colour:	white	CE certificate:	380/2023
Material of the body:	ABS	Autotest:	yes
Colour of the body:	white	Warranty [years]:	2 / 0.5 (battery)
Ring material:	ABS	Manual:	Download PDF
Ring colour:	white	PZH certificate:	B-BK-60212-0619/20
Dimensions (H/W/T/S) [mm]:	340/115	ENEC Certificate:	
Mounting dimensions [mm]:	140		
Impact resistance:	IK10		
Ingress protection:	IP65		

LIGHT CURVES



DIONE LED PLUS ASYMMETRIC DP 2150LM 830 IP65 I KL. RCR AW 3H AT OPAL WHITE 21W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 380/2023