

DIONE LED PLUS ASYMMETRIC DP 2300LM 840 IP65 I KL. AW 3H AT OPAL WHITE 21W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	940170
Nominal power [W]:	21
Luminous flux [lm]*:	2300
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS ASYMMETRIC DP 2300LM 840 IP65 I KL. AW 3H AT OPAL WHITE 21W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	940170	Ingress protection:	IP65
Light source:	LED module	Mounting version:	surface
Nominal power [W]:	21	Working temperature [°C]:	from 0 to +25
Rated power of the luminaire [W]:	22	Dimensions of single box [mm]:	340/340/115
Supply voltage [V]:	220-240	Net weight [kg]:	1.250
Frequency [Hz]:	50 - 60	Warranty [years]:	2 / 0.5 (bateria)
Luminous flux [lm]:	2300	Permeability factor of the diffuser:	0.73
Luminous efficacy [lm/W]:	105	Category type:	bulkheads
Energy efficiency class:	E	Category of application:	educational institutions, commercial facilities
Electrical protection class:	I	Version:	DP
Colour temperature [K]:	4000	AC voltage range [V]:	198-264
Color rendering index (Ra) >:	80	DC voltage range [V]:	176-280
SDCM:	3	LED lifespan L70B50 [h]:	115000
Power factor:	0.94	LED lifespan L80B10 [h]:	75000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	33000
Surge protection [kV]:	1	Light distribution type:	asymmetric
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	OPAL	CE certificate:	380/2023
Diffuser colour:	white	Emergency lighting [h]:	3
Material of the body:	ABS	Autotest:	yes
Colour of the body:	white	Warranty [years]:	2 / 0.5 (battery)
Ring material:	ABS	ENEC Certificate:	
Ring colour:	white	Environmental Product Declaration (EPD):	944/2026
Dimensions (H/W/T/S) [mm]:	340/115	Manual:	Download PDF
Mounting dimensions [mm]:	140	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Impact resistance:	IK10		

LIGHT CURVES



DIONE LED PLUS ASYMMETRIC DP 2300LM 840 IP65 I KL. AW 3H AT OPAL WHITE 21W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 380/2023