

PIATTO SURFACE-MOUNTED FI 610MM 2040LM I KL. BLACK-GOLD IP20 830 (28W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	670008
Ingress protection:	IP20
Nominal power [W]:	28
Luminous flux [lm]*:	2050
Colour temperature [K]:	3000
Colour rendering index:	>80
SDCM:	≤ 3
Colour of the body:	black and gold

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. Possibility of surface and suspended mounting allows various applications. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use. Optionally, there are versions equipped with a microwave motion sensor (RCR) and the possibility of control via the DALI protocol, increasing the energy-saving and functional properties of the luminaires.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.

PIATTO SURFACE-MOUNTED FI 610MM 2040LM I KL. BLACK-GOLD IP20 830 (28W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	28	Ingress protection:	IP20
Rated power of the luminaire [W]:	29	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -25 to +35
Frequency [Hz]:	50 - 60	CE certificate:	220/2023
Luminous flux [lm]:	2050	Index:	670008
Luminous efficacy [lm/W]:	71	Category type:	architectural, downlights
Energy efficiency class:	G	Diffuser colour:	white
Electrical protection class:	I	Optics material:	PC
Colour temperature [K]:	3000	Optics:	matrix lens
Colour rendering index:	>80	Accessories included:	mounting pins
SDCM:	≤ 3	Net weight [kg]:	7.500
Power factor:	0.91	Warranty [years]:	5
Diffuser material:	PMMA	LED lifespan L70B50 [h]:	120000
Diffuser type:	OPAL	LED lifespan L80B20 [h]:	80000
Material of the body:	powder coated aluminium	LED lifespan L90B10 [h]:	40000
Colour of the body:	black and gold	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	ø610/150	Manual:	Download PDF

Card creation date: 07 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 220/2023