

PIATTO SURFACE-MOUNTED FI 610MM RCR 2200LM I KL. WHITE-GOLD IP20 840 (28W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-------------------------|---|
| Index: | x |
| Ingress protection: | IP20 |
| Nominal power [W]: | 28 |
| Luminous flux [lm]*: | 2050 - 3500 |
| Colour temperature [K]: | 3000; 4000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Colour of the body: | biało-złoty; czarno-srebrny; czarno-złoty |
| DIMM DALI: | yes |
| Motion sensor: | yes |

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. Possibility of surface and suspended mounting allows various applications. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use. Optionally, there are versions equipped with a microwave motion sensor (RCR) and the possibility of control via the DALI protocol, increasing the energy-saving and functional properties of the luminaires.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.

PIATTO SURFACE-MOUNTED FI 610MM RCR 2200LM I KL. WHITE-GOLD IP20 840 (28W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|------------------------------|---|--------------------------|-----------------------------------|
| Nominal power [W]: | 28 | Index: | x |
| Supply voltage [V]: | 220-240 | EAN: | x |
| Frequency [Hz]: | 50-60 | Category type: | architectural, downlights |
| Luminous flux [lm]: | 2050 - 3500 | Motion sensor: | yes |
| Energy efficiency class: | F; G | Cable length [m]: | 1.50 |
| Electrical protection class: | I | ETIM class: | EC001743; EC002892 |
| Colour temperature [K]: | 3000; 4000 | Diffuser colour: | biały |
| Colour rendering index: | >80 | Optics material: | PC |
| SDCM: | ≤ 3 | Optics: | matryca soczewkowa |
| Power factor: | 0.88; 0.91; 0.93; 0.96 | Accessories included: | mounting pins; suspension set |
| Diffuser material: | HIPS; PMMA | Net weight [kg]: | 7.500; 7.600; 7.700; 7.800; 7.900 |
| Diffuser type: | OPAL | Warranty [years]: | 5 |
| Material of the body: | Aluminium malowane proszkowo | AC voltage range [V]: | 198-264 |
| Colour of the body: | biało-złoty; czarno-srebrny; czarno-złoty | DC voltage range [V]: | 170-280 |
| Dimensions (H/W/T/S) [mm]: | ø610/150; ø610/150/1500 | LED lifespan L70B50 [h]: | 120000 |
| Ingress protection: | IP20 | LED lifespan L80B20 [h]: | 80000 |
| Mounting version: | natynkowy; zwieszany | LED lifespan L90B10 [h]: | 40000 |
| Working temperature [°C]: | od -25 do +25; od -25 do +35 | Warranty [years]: | 5 |
| DIMM DALI: | yes | Manual: | Download PDF |
| CE certificate: | 83/2020 | | |

Card creation date: 05 May 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 220/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl