

PIATTO SURFACE-MOUNTED FI 610MM RCR 2970LM I KL. BLACK-GOLD IP20 830 (45W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|--------------------------------|----------------|
| Index: | 670244 |
| Ingress protection: | IP20 |
| Nominal power [W]: | 45 |
| Luminous flux [lm]*: | 2950 |
| Colour temperature [K]: | 3000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Colour of the body: | black and gold |
| Motion sensor: | yes |

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. Possibility of surface and suspended mounting allows various applications. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use. Optionally, there are versions equipped with a microwave motion sensor (RCR) and the possibility of control via the DALI protocol, increasing the energy-saving and functional properties of the luminaires.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.


PIATTO SURFACE-MOUNTED FI 610MM RCR 2970LM I KL. BLACK-GOLD IP20 830 (45W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|-------------------------|---------------------------|------------------------------|
| Nominal power [W]: | 45 | Ingress protection: | IP20 |
| Colour temperature [K]: | 3000 | Mounting version: | surface |
| Rated power of the luminaire [W]: | 46 | Working temperature [°C]: | from -25 to +35 |
| Luminous flux [lm]: | 2950 | CE certificate: | 220/2023 |
| Supply voltage [V]: | 220-240 | Index: | 670244 |
| Frequency [Hz]: | 50 - 60 | Category type: | architectural, downlights |
| Motion sensor: | yes | Diffuser colour: | white |
| Luminous efficacy [lm/W]: | 65 | Optics material: | PC |
| Colour of the body: | black and gold | Optics: | matrix lens |
| Energy efficiency class: | G | Accessories included: | mounting pins |
| Electrical protection class: | I | Net weight [kg]: | 7.600 |
| Colour rendering index: | >80 | Warranty [years]: | 5 |
| SDCM: | ≤ 3 | LED lifespan L70B50 [h]: | 120000 |
| Power factor: | 0.93 | LED lifespan L80B20 [h]: | 80000 |
| Diffuser material: | PMMA | LED lifespan L90B10 [h]: | 40000 |
| Diffuser type: | OPAL | Warranty [years]: | 5 |
| Material of the body: | powder coated aluminium | Manual: | Download PDF |
| Dimensions (H/W/T/S) [mm]: | ø610/150 | Plik LDT: | Download |

LIGHT CURVES



Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 220/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl