PIATTO SUSPENDED FI 610MM 2040LM I KL. BLACK-GOLD IP 20 830 (28W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	670305
Ingress protection:	IP20
Nominal power [W]:	28
Luminous flux [lm]*:	2050
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3

black and gold

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. Possibility of surface and suspended mounting allows various applications. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use. Optionally, there are versions equipped with a microwave motion sensor (RCR) and the possibility of control via the DALI protocol, increasing the energy-saving and functional properties of the luminaires.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.



Colour of the body:

PIATTO SUSPENDED FI 610MM 2040LM I KL. BLACK-GOLD IP 20 830 (28W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	28
Rated power of the luminaire [W]:	29
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	2050
Luminous efficacy [lm/W]:	71
Energy efficiency class:	G
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.91
Diffuser material:	PMMA
Diffuser type:	OPAL
Material of the body:	powder coated aluminium
Colour of the body:	black and gold
Dimensions (H/W/T/S) [mm]:	ø610/150/1500
Ingress protection:	IP20

Mounting version:	suspended
Working temperature [°C]:	from -25 to +35
CE certificate:	220/2023
Index:	670305
Category type:	decorative fixtures
Diffuser colour:	white
Optics material:	PC
Optics:	matrix lens
Accessories included:	suspension set
Net weight [kg]:	7.700
Warranty [years]:	5
LED lifespan L70B50 [h]:	120000
LED lifespan L80B20 [h]:	80000
LED lifespan L90B10 [h]:	40000
Warranty [years]:	5
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 12 May 2025



