

PIATTO SUSPENDED FI 610MM 2200LM I KL. WHITE-GOLD IP20 840 (28W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	670374
Ingress protection:	IP20
Nominal power [W]:	28
Luminous flux [lm]*:	2200
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Colour of the body:	white-gold

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. Possibility of surface and suspended mounting allows various applications. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use. Optionally, there are versions equipped with a microwave motion sensor (RCR) and the possibility of control via the DALI protocol, increasing the energy-saving and functional properties of the luminaires.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.

PIATTO SUSPENDED FI 610MM 2200LM I KL. WHITE-GOLD IP20 840 (28W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	28	Mounting version:	suspended
Rated power of the luminaire [W]:	29	Working temperature [°C]:	from -25 to +35
Supply voltage [V]:	220-240	CE certificate:	220/2023
Frequency [Hz]:	50 - 60	Index:	670374
Luminous flux [lm]:	2200	Category type:	decorative fixtures
Luminous efficacy [lm/W]:	76	Diffuser colour:	white
Energy efficiency class:	F	Optics material:	PC
Electrical protection class:	I	Optics:	matrix lens
Colour temperature [K]:	4000	Accessories included:	suspension set
Color rendering index (Ra) >:	80	Net weight [kg]:	7.700
SDCM:	3	Warranty [years]:	5
Power factor:	0.91	LED lifespan L70B50 [h]:	120000
Diffuser material:	PMMA	LED lifespan L80B10 [h]:	80000
Diffuser type:	OPAL	LED lifespan L90B10 [h]:	40000
Material of the body:	powder coated aluminium	Warranty [years]:	5
Colour of the body:	white-gold	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	ø610/150/1500	Plik LDT:	Download
Ingress protection:	IP20		

Card creation date: 12 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 220/2023