

PIATTO SUSPENDED FI 610MM 3200LM I KL. WHITE-GOLD

IP20 840 (45W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	670435
Ingress protection:	IP20
Nominal power [W]:	45
Luminous flux [lm]*:	3200
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Colour of the body:	white-gold

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. Possibility of surface and suspended mounting allows various applications. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use. Optionally, there are versions equipped with a microwave motion sensor (RCR) and the possibility of control via the DALI protocol, increasing the energy-saving and functional properties of the luminaires.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.


PIATTO SUSPENDED FI 610MM 3200LM I KL. WHITE-GOLD IP20 840 (45W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	45	Ingress protection:	IP20
Colour temperature [K]:	4000	Mounting version:	suspended
Rated power of the luminaire [W]:	46	Working temperature [°C]:	from -25 to +35
Luminous flux [lm]:	3200	CE certificate:	220/2023
Supply voltage [V]:	220-240	Index:	670435
Frequency [Hz]:	50 - 60	Category type:	architectural, downlights
Luminous efficacy [lm/W]:	70	Diffuser colour:	white
Colour of the body:	white-gold	Optics material:	PC
Energy efficiency class:	G	Optics:	matrix lens
Electrical protection class:	I	Accessories included:	suspension set
Colour rendering index:	>80	Net weight [kg]:	7.800
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.93	LED lifespan L70B50 [h]:	120000
Diffuser material:	PMMA	LED lifespan L80B20 [h]:	80000
Diffuser type:	OPAL	LED lifespan L90B10 [h]:	40000
Material of the body:	powder coated aluminium	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	ø610/150/1500	Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES



Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 220/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl