

# OCULUS LED 34650LM 840 IP23 I KL. AW 3H 75D SP10KV 206W

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |                         |
|-------------------------------------|-------------------------|
| <b>Index:</b>                       | 964350                  |
| <b>Nominal power [W]:</b>           | 206                     |
| <b>Luminous flux [lm]*:</b>         | 34650                   |
| <b>Colour temperature [K]:</b>      | 4000                    |
| <b>Electrical protection class:</b> | I                       |
| <b>Energy efficiency class:</b>     | C                       |
| <b>Material of the body:</b>        | powder coated aluminium |
| <b>Diffuser material:</b>           | PC                      |
| <b>Beam angle [°]:</b>              | 75                      |
| <b>Working temperature [°C]:</b>    | from 0 to +25           |

## CHARACTERISTICS

OCULUS LED is a HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder coated – uses natural conduction and convection processes, which have a positive effect on luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work in an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency: max 176 lm/W. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise linear lenses made of polycarbonate (PC). There are 3 dedicated ranges of light distribution available: 55°, 75°, 105°. GLASS version with tempered glass (without lenses) and 105° distribution is also available.

Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

## APPLICATION

The luminaire is intended for suspended mounting (using chains, wires, etc.) both indoors and outdoors. It will prove perfect for manufacturing plants and halls as well as large-format warehouses and logistics centres.

# OCULUS LED 34650LM 840 IP23 I KL. AW 3H 75D SP10KV 206W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |                         |                                |   |
|-----------------------------------|-------------------------|--------------------------------|---|
| Nominal power [W]:                | 206                     | Mounting version:              | suspended   |
| Index:                            | 964350                  | Cable length [m]:              | 0.30  |
| Colour temperature [K]:           | 4000                    | Dimensions of single box [mm]: | 175/400/400   |
| Luminous flux [lm]:               | 34650                   | Net weight [kg]:               | 5.850   |
| Light source:                     | LED module              | Category type:                 | high-bay and low-bay  |
| Diffuser material:                | PC                      | AC voltage range [V]:          | 198-264   |
| Rated power of the luminaire [W]: | 224                     | DC voltage range [V]:          | 176-280   |
| Beam angle [°]:                   | 75                      | LED lifespan L70B50 [h]:       | 196000  |
| Supply voltage [V]:               | 220-240                 | LED lifespan L80B20 [h]:       | 123000  |
| Frequency [Hz]:                   | 50 - 60                 | LED lifespan L90B10 [h]:       | 60000   |
| Working temperature [°C]:         | from 0 to +25           | Accessories included:          | Eye bolt  |
| Luminous efficacy [lm/W]:         | 160                     | Photobiological safety:        | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Energy efficiency class:          | C                       | Charging time [h:min]:         | 1   |
| Electrical protection class:      | I                       | Battery life [h:min]:          | 3   |
| Colour rendering index:           | >80                     | Battery:                       | NiMh  |
| SDCM:                             | ≤ 3                     | Battery capacity [mAh]:        | 4   |
| Power factor:                     | 0.95                    | Emergency lighting [h]:        | 3   |
| Surge protection [kV]:            | 10                      | Autotest:                      | 1   |
| Diffuser type:                    | transparent             | Operating mode:                | M   |
| Diffuser colour:                  | transparent             | ETIM class:                    | EC001716  |
| Optics material:                  | PC                      | The number of implement units: | 2   |
| Optics:                           | lens                    | Warranty [years]:              | 2 / 0.5 (bateria)   |
| Material of the body:             | powder coated aluminium | ENEC Certificate:              | <a href="#">PL BBJ/005/2021/M1</a>  |
| Colour of the body:               | grey                    | CE certificate:                | <a href="#">153/2023</a>  |
| Dimensions (H/W/T/S) [mm]:        | 595/371                 | PZH certificate:               | <a href="#">B-BK-60212-0481/21</a>  |
| Impact resistance:                | IK09                    | HACCP:                         | <a href="#">852/2004</a>  |
| Ingress protection:               | IP23                    | Manual:                        | <a href="#">Download PDF</a>  |

# OCULUS LED 34650LM 840 IP23 I KL. AW 3H 75D SP10KV 206W

DETAILED CARD

## ACCESSORIES AVAILABLE

| index   | Name  |
|---------|---|
| 964244  | OCULUS LED - RCR motion sensor  |
| 964886  | OCULUS LED - universal handle-lack of compatibility with Dali version 294W        |
| 964893  | OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W |
| 964862  | OCULUS LED - protective grid  |
| 963674  | OCULUS LED - RCR / PIR DALI motion sensor   |
| WSEL438 | Remote control for motion sensor HD01R  |
| WSEL415 | WSEL415 Remote control for - PIR sensor   |



OCULUS LED - RCR motion sensor (964244)



OCULUS LED - universal handle-lack of compatibility with Dali version 294W (964886)



OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W (964893)



OCULUS LED - protective grid (964862)



OCULUS LED - RCR / PIR DALI motion sensor (963674)



Remote control for motion sensor HD01R (WSEL438)



WSEL415 Remote control for - PIR sensor (WSEL415)

Card creation date: 11 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 153/2023