OCULUS LED 35850LM 840 IP23 I KL. AW 3H 105D SP10KV 206W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	964367
--------	--------

Nominal power [W]: 206

Luminous flux [lm]*: 35850

Colour temperature [K]: 4000

Electrical protection class:

Energy efficiency class:

Material of the body: powder coated aluminium

Diffuser material: PC

Beam angle [°]: 105

Working temperature [°C]: from 0 to +25

CHARACTERISTICS

OCULUS LED is a HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body — made of die-cast aluminium and powder coated — uses natural conduction and convection processes, which have a positive effect on luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work in an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency: max 176 lm/W. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise linear lenses made of polycarbonate (PC). There are 3 dedicated ranges of light distribution available: 55°, 75°, 105°. GLASS version with tempered glass (without lenses) and 105° distribution is also available.

Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

APPLICATION

The luminaire is intended for suspended mounting (using chains, wires, etc.) both indoors and outdoors. It will prove perfect for manufacturing plants and halls as well as large-format warehouses and logistics centres.



OCULUS LED 35850LM 840 IP23 I KL. AW 3H 105D SP10KV 206W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	964367
Light source:	LED module
Nominal power [W]:	206
Rated power of the luminaire [W]:	224
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	35850
Luminous efficacy [lm/W]:	165
Energy efficiency class:	В
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.95
Beam angle [°]:	105
Surge protection [kV]:	4
Diffuser material:	PC
Diffuser type:	transparent
Diffuser colour:	transparent
Material of the body:	powder coated aluminium
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	595/371
Impact resistance:	IK09
Ingress protection:	IP23
Mounting version:	suspended
Working temperature [°C]:	from 0 to +25
The number of implement units:	2

Cable length [m]:	0.30	
Dimensions of single box [mm]:	175/400/400	
Net weight [kg]:	5.850	
Category type:	high-bay and low-bay	
AC voltage range [V]:	198-264	
DC voltage range [V]:	176-280	
LED lifespan L70B50 [h]:	196000	
LED lifespan L80B20 [h]:	123000	
LED lifespan L90B10 [h]:	60000	
Accessories included:	Eye bolt	
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)	
Charging time [h:min]:	1	
Battery life [h:min]:	3	
Battery:	NiMh	
Battery capacity [mAh]:	4	
Emergency lighting [h]:	3	
Autotest:	yes	
Operating mode:	M	
ETIM class:	EC001716	
Warranty [years]:	2 / 0.5 (bateria)	
ENEC Certificate:	PL BBJ/005/2021/M1	
CE certificate:	<u>153/2023</u>	
PZH certificate:	B-BK-60212-0481/21	
HACCP:	<u>852/2004</u>	
Environmental Product Declaration (EPD):	816/2025	
Manual:	<u>Download PDF</u>	



OCULUS LED 35850LM 840 IP23 I KL. AW 3H 105D SP10KV 206W


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
964244	OCULUS LED - RCR motion sensor
964886	OCULUS LED - universal handle-lack of compatibility with Dali version 294W
964893	OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W
964862	OCULUS LED - protective grid
963674	OCULUS LED - RCR / PIR DALI motion sensor
WSEL438	Remote control for motion sensor HD01R
WSEL415	WSEL415 Remote control for - PIR sensor




OCULUS LED - RCR motion sensor (964244)



OCULUS LED - universal handle-lack of compatibility with Dali version 294W (964886)



OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W (964893)



OCULUS LED - protective grid (964862)



OCULUS LED - RCR / PIR DALI motion sensor (963674)



Remote control for motion sensor HD01R (WSEL438)



WSEL415 Remote control for - PIR sensor (WSEL415)

Card creation date: 10 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

