

DIONE LED PLUS MULTI 1650-2610LM 830 IP65 I KL. RCR OPAL WHITE 22W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W] - range:	15/18/22/26
Colour temperature [K]:	3000
Luminous flux of the luminaire [lm] - range:	1650/1900/2300/2610
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS
Diffuser material:	PC

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor). The MULTI luminaire version allows individual configuration: thanks to the built-in micoswitch, it is possible to choose one of 4 settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS MULTI 1650-2610LM 830 IP65 I KL. RCR OPAL WHITE 22W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W] - range:	15/18/22/26	Dimensions (H/W/T/S) [mm]:	340/115
Index:	951831	Mounting dimensions [mm]:	140
Colour temperature [K]:	3000	Impact resistance:	IK10
Luminous flux of the luminaire [lm] - range:	1650/1900/2300/2610	Ingress protection:	IP65
Diffuser type:	OPAL	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Dimensions of single box [mm]:	340/340/115
Frequency [Hz]:	50 - 60	Number on the palette [pcs]:	80
Motion sensor:	1	Permeability factor of the diffuser:	0.73
Luminous efficacy [lm/W]:	103	Category type:	bulkheads
Energy efficiency class:	E	Category of application:	commercial facilities, educational institutions
Electrical protection class:	I	LED lifespan L70B50 [h]:	110000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	84000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	33000
Power factor:	0.91	Light distribution type:	open space
Beam angle [°]:	120	Light source:	LED module
Diffuser material:	PC	Max load (RCR) [W]:	400
Diffuser colour:	white	Surge protection [kV]:	1
Material of the body:	ABS	Mounting version:	surface
Colour of the body:	white	Net weight [kg]:	1.250
Ring material:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ring colour:	white	Warranty [years]:	5
		CE certificate:	379/2023
		PZH certificate:	B-BK-60212-0619/20
		Manual:	Download PDF
		Plik LDT:	Pobierz

DIONE LED PLUS MULTI 1650-2610LM 830 IP65 I KL. RCR OPAL WHITE 22W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 17 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 379/2023