

# DIONE LED PLUS MULTI 1650-2650LM 840 IP65 I KL. OPAL WHITE 22W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK10
<b>Nominal power [W] - range:</b>	15/18/22/26
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux of the luminaire [lm] - range:</b>	1650/2000/2320/2650
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Ring material:</b>	ABS
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor). The MULTI luminaire version allows individual configuration: thanks to the built-in microswitch, it is possible to choose one of 4 settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

# DIONE LED PLUS MULTI 1650-2650LM 840 IP65 I KL. OPAL WHITE 22W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Nominal power [W] - range:</b>	15/18/22/26	<b>Colour of the body:</b>	white
<b>Index:</b>	951794	<b>Ring material:</b>	ABS
<b>Colour temperature [K]:</b>	4000	<b>Ring colour:</b>	white
<b>EAN:</b>	5905963951794	<b>Dimensions (H/W/T/S) [mm]:</b>	340x115
<b>Luminous flux of the luminaire [lm] - range:</b>	1650/2000/2320/2650	<b>Mounting dimensions [mm]:</b>	140
<b>Diffuser type:</b>	OPAL	<b>Impact resistance:</b>	IK10
<b>Supply voltage [V]:</b>	220-240	<b>Ingress protection:</b>	IP65
<b>Frequency [Hz]:</b>	50 - 60	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Luminous efficacy [lm/W]:</b>	107	<b>Dimensions of single box [mm]:</b>	340/340/115
<b>Energy efficiency class:</b>	E	<b>Number on the palette [pcs]:</b>	80
<b>Electrical protection class:</b>	I	<b>Permeability factor of the diffuser:</b>	0.73
<b>Colour rendering index:</b>	>80	<b>Category type:</b>	bulkheads
<b>SDCM:</b>	≤ 3	<b>Category of application:</b>	commercial facilities, educational institutions
<b>Power factor:</b>	0.95	<b>LED lifespan L70B50 [h]:</b>	110000
<b>Beam angle [°]:</b>	120	<b>LED lifespan L80B20 [h]:</b>	84000
<b>Diffuser material:</b>	PC	<b>LED lifespan L90B10 [h]:</b>	33000
<b>Diffuser colour:</b>	white	<b>Light distribution type:</b>	open space
<b>Material of the body:</b>	ABS	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		<b>Warranty [years]:</b>	5
		<b>CE certificate:</b>	<a href="#">379/2023</a>
		<b>PZH certificate:</b>	<a href="#">B-BK-60212-0619/20</a>
		<b>Manual:</b>	<a href="#">Download PDF</a>
		<b>Plik LDT:</b>	<a href="#">Download</a>

# DIONE LED PLUS MULTI 1650-2650LM 840 IP65 I KL. OPAL WHITE 22W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white  
matt RAL 9003 painted vandal  
resistant (120DL118)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 379/2023