


# SQ 600 LED 4100LM PLX RCR I KL. IP20 592X592MM 830 (45W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	668319
Ingress protection:	IP44/IP20
Nominal power [W]:	45
Luminous flux [lm]*:	4100
Colour rendering index:	80
SDCM:	≤ 5
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

## CHARACTERISTICS

SQ 600 LED is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

The luminaire is available in 2 versions:

- with OPAL diffuser - providing soft light;
- with PRM diffuser - with higher luminous efficiency and low glare UGR <19 (18W, 24W, 32W versions).

Available options:

- RCR sensor - sensor used for motion detection, without twilight detection option; uses microwaves for detection (active sensor),
- control in the DALI standard,
- CORRIDOR corridor function (RCR + DALI).

The ingress protection- depends on the method of installation:

- surface mounted - IP20,
- flush-mounted - IP44/20.

## APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


# SQ 600 LED 4100LM PLX RCR I KL. IP20 592X592MM 830 (45W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	668319	Mounting dimensions [mm]:	563/297
Light source:	LED module	Ingress protection:	IP44/IP20
Nominal power [W]:	45	Glow wire test [°C]:	650
Rated power of the luminaire [W]:	51.50	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.900
Luminous flux [lm]:	4100	Category type:	troffers
Luminous efficacy [lm/W]:	80	Category of application:	educational institutions, commercial facilities
Energy efficiency class:	F	AC voltage range [V]:	90-175
Electrical protection class:	I	DC voltage range [V]:	198 - 264
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	50000
Colour rendering index:	80	LED lifespan L80B20 [h]:	32000
SDCM:	≤ 5	LED lifespan L90B10 [h]:	15000
Power factor:	0.98	Light distribution type:	open space
Diffuser material:	PS	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser type:	OPAL	Technical Warranty:	5
Diffuser colour:	white	PZH certificate:	<a href="#">B-BK-60212-0618/20</a>
Optics material:	PMMA	CE certificate:	<a href="#">110/2023</a>
Optics:	lens	Manual:	<a href="#">Download PDF</a>
Material of the body:	ABS	ENEC Certificate:	<a href="#">PL BBJ/006/2021/M1</a>
Colour of the body:	white	Plik LDT:	<a href="#">Download</a>
Dimensions (H/W/T/S) [mm]:	592/592/44		

## LIGHT CURVES



# SQ 600 LED 4100LM PLX RCR I KL. IP20 592X592MM 830 (45W)


DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
978395	Installation kit SQ 600 Ceiling system H40 100x100
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 01 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 110/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl