

# SQ 600 LED 4700LM PRM DALI I KL. IP20 592X592MM 840 (32W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	668531
<b>Ingress protection:</b>	IP44/IP20
<b>Nominal power [W]:</b>	32
<b>Luminous flux [lm]*:</b>	4700
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	PRM

## CHARACTERISTICS

SQ 600 LED is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

The luminaire is available in 2 versions:

- with OPAL diffuser - providing soft light;
- with PRM diffuser - with higher luminous efficiency and low glare UGR <19 (18W, 24W, 32W versions).

Available options:

- RCR sensor - sensor used for motion detection, without twilight detection option; uses microwaves for detection (active sensor),
- control in the DALI standard,
- CORRIDOR corridor function (RCR + DALI).

The ingress protection- depends on the method of installation:

- surface mounted - IP20,
- flush-mounted - IP44/20.

## APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

# SQ 600 LED 4700LM PRM DALI I KL. IP20 592X592MM 840 (32W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	668531	Ingress protection:	IP44/IP20
Light source:	LED module	Glow wire test [°C]:	650
Nominal power [W]:	32	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Rated power of the luminaire [W]:	33	DIMM DALI:	yes
Supply voltage [V]:	220-240	Net weight [kg]:	2.230
Frequency [Hz]:	50 - 60	Category type:	troffers
Luminous flux [lm]:	4700	Category of application:	educational institutions, commercial facilities
Luminous efficacy [lm/W]:	142	LED lifespan L70B50 [h]:	132000
Energy efficiency class:	C	LED lifespan L80B10 [h]:	84000
Electrical protection class:	I	LED lifespan L90B10 [h]:	42000
Colour temperature [K]:	4000	Light distribution type:	open space
Color rendering index (Ra) >:	80	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	3	Technical Warranty:	5
Power factor:	0.95	CE certificate:	<a href="#">110/2023</a>
Diffuser material:	PS	ENEC Certificate:	<a href="#">PL_BBJ/006/2021/M1/A1</a>
Diffuser type:	PRM	PZH certificate:	<a href="#">B-BK-60112-0419/2025</a>
Diffuser colour:	transparent	Environmental Product Declaration (EPD):	<a href="#">944/2026</a>
Material of the body:	ABS	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	592/592/44	Plik LDT:	<a href="#">Download</a>
Mounting dimensions [mm]:	563/297		

## LIGHT CURVES



# SQ 600 LED 4700LM PRM DALI I KL. IP20 592X592MM 840 (32W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
978395	Installation kit SQ 600 Ceiling system H40 100x100
374845	Frame adapter KG 635x635 WHITE
998966	"Frame steel white structure RAL9016 600x600 SM ""well effect""
998973	Frame steel white gloss RAL9016 600x600 SM "well effect"



Frame adapter KG 635x635  
WHITE (374845)



"Frame steel white structure RAL9016  
600x600 SM ""well effect"" (998966)



Frame steel white gloss RAL9016  
600x600 SM "well effect" (998973)

Card creation date: 12 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 110/2023