

SQ 600 LED 6350LM PRM DALI I KL. IP20 592X592MM 830 (52W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	669026
Ingress protection:	IP44/IP20
Nominal power [W]:	52
Luminous flux [lm]*:	6350
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	D
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	PRM

CHARACTERISTICS

SQ 600 LED is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

The luminaire is available in 2 versions:

- with OPAL diffuser - providing soft light;
- with PRM diffuser - with higher luminous efficiency and low glare UGR <19 (18W, 24W, 32W versions).

Available options:

- RCR sensor - sensor used for motion detection, without twilight detection option; uses microwaves for detection (active sensor),
- control in the DALI standard,
- CORRIDOR corridor function (RCR + DALI).

The ingress protection- depends on the method of installation:

- surface mounted - IP20,
- flush-mounted - IP44/20.

APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

SQ 600 LED 6350LM PRM DALI I KL. IP20 592X592MM 830 (52W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	669026	Mounting dimensions [mm]:	563/297
Light source:	LED module	Ingress protection:	IP44/IP20
Nominal power [W]:	52	Glow wire test [°C]:	650
Rated power of the luminaire [W]:	53	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Supply voltage [V]:	220-240	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.230
Luminous flux [lm]:	6350	Category type:	troffers
Luminous efficacy [lm/W]:	120	Category of application:	educational institutions, commercial facilities
Energy efficiency class:	D	LED lifespan L70B50 [h]:	132000
Electrical protection class:	I	LED lifespan L80B10 [h]:	84000
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	42000
Color rendering index (Ra) >:	80	Light distribution type:	open space
SDCM:	3	Technical Warranty:	5
Power factor:	0.95	CE certificate:	110/2023
Diffuser material:	PS	ENEC Certificate:	PL BBJ/006/2021/M1/A1
Diffuser type:	PRM	PZH certificate:	B-BK-60112-0419/2025
Diffuser colour:	transparent	Environmental Product Declaration (EPD):	944/2026
Material of the body:	ABS	Manual:	Download PDF
Colour of the body:	white	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	592/592/44	Plik LDT:	Download

LIGHT CURVES



SQ 600 LED 6350LM PRM DALI I KL. IP20 592X592MM 830 (52W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
978395	Installation kit SQ 600 Ceiling system H40 100x100
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 04 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 110/2023