

# SQ 600 LED 6800LM PRM I KL. IP20 592X592MM 840 (52W) RAL9005

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	669057
<b>Ingress protection:</b>	IP44/IP20
<b>Nominal power [W]:</b>	52
<b>Luminous flux [lm]*:</b>	6800
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	PRM

## CHARACTERISTICS

SQ 600 LED is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

The luminaire is available in 2 versions:

- with OPAL diffuser - providing soft light;
- with PRM diffuser - with higher luminous efficiency and low glare UGR <19 (18W, 24W, 32W versions).

Available options:

- RCR sensor - sensor used for motion detection, without twilight detection option; uses microwaves for detection (active sensor),
- control in the DALI standard,
- CORRIDOR corridor function (RCR + DALI).

The ingress protection- depends on the method of installation:

- surface mounted - IP20,
- flush-mounted - IP44/20.

## APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

# SQ 600 LED 6800LM PRM I KL. IP20 592X592MM 840 (52W) RAL9005

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	669057	<b>Mounting dimensions [mm]:</b>	563/297
<b>Light source:</b>	LED module	<b>Ingress protection:</b>	IP44/IP20
<b>Nominal power [W]:</b>	52	<b>Glow wire test [°C]:</b>	650
<b>Rated power of the luminaire [W]:</b>	53	<b>Mounting version:</b>	surface mounted; recessed mounted in modular ceiling possible
<b>Supply voltage [V]:</b>	220-240	<b>Net weight [kg]:</b>	1.730
<b>Frequency [Hz]:</b>	50 - 60	<b>Category type:</b>	troffers
<b>Luminous flux [lm]:</b>	6800	<b>Category of application:</b>	educational institutions, commercial facilities
<b>Luminous efficacy [lm/W]:</b>	128	<b>LED lifespan L70B50 [h]:</b>	132000
<b>Energy efficiency class:</b>	D	<b>LED lifespan L80B10 [h]:</b>	84000
<b>Electrical protection class:</b>	I	<b>LED lifespan L90B10 [h]:</b>	42000
<b>Colour temperature [K]:</b>	4000	<b>Light distribution type:</b>	open space
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Technical Warranty:</b>	5
<b>SDCM:</b>	3	<b>CE certificate:</b>	<a href="#">110/2023</a>
<b>Power factor:</b>	0.95	<b>ENEC Certificate:</b>	<a href="#">PL_BB/J/006/2021/M1/A1</a>
<b>Diffuser material:</b>	PS	<b>PZH certificate:</b>	<a href="#">B-BK-60112-0419/2025</a>
<b>Diffuser type:</b>	PRM	<b>Environmental Product Declaration (EPD):</b>	<a href="#">944/2026</a>
<b>Diffuser colour:</b>	transparent	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Material of the body:</b>	ABS	<b>ISO Certificates:</b>	9001:2015, 14001:2015, 45001:2018, 50001:2018
<b>Colour of the body:</b>	black mat	<b>Plik LDT:</b>	<a href="#">Download</a>
<b>Dimensions (H/W/T/S) [mm]:</b>	592/592/44		

# SQ 600 LED 6800LM PRM I KL. IP20 592X592MM 840 (52W) RAL9005

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
978395	Installation kit SQ 600 Ceiling system H40 100x100
374845	Frame adapter KG 635x635 WHITE
998966	"Frame steel white structure RAL9016 600x600 SM ""well effect""
998973	Frame steel white gloss RAL9016 600x600 SM "well effect"



Frame adapter KG 635x635  
WHITE (374845)



"Frame steel white structure RAL9016  
600x600 SM ""well effect"" (998966)



Frame steel white gloss RAL9016  
600x600 SM "well effect" (998973)

Card creation date: 12 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 110/2023