

TERRA 2 LED N 595X595MM X4 5500LM 830 BLACK MAT STRUCTURE (72W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|----------------------------|---------------------|
| Index: | 239793 |
| Ingress protection: | IP20 |
| Nominal power [W]: | 72 |
| Luminous flux [lm]*: | 5500 |
| SDCM: | ≤ 3 |
| Material of the body: | powder coated steel |
| Optics: | black HE |
| Mounting version: | surface |
| Dimensions (H/W/T/S) [mm]: | 595/595/36 |

CHARACTERISTICS

Recessed square LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter), or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

UGR <19

Unified Glare Rating is an indicator characterizing glare. The lower the Unified Lighting Rating Index (UGR), the lower the glare. In the case of luminaires designed for office spaces, UGR <19, among, others improves the comfort of work, reduces errors and fatigue. The UGR value also depends on many factors characterizing the room and the location of the observer. Special computer programs should be used to precisely determine the degree of glare for specific conditions.

APPLICATION

General-purpose recessed luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

TERRA 2 LED N 595X595MM X4 5500LM 830 BLACK MAT STRUCTURE (72W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------------|---------------------------|---|
| Index: | 239793 | Ingress protection: | IP20 |
| Light source: | LED module | Mounting version: | surface |
| Nominal power [W]: | 72 | Working temperature [°C]: | from -20 to +35 |
| Rated power of the luminaire [W]: | 79.70 | Category type: | louvres |
| Supply voltage [V]: | 220-240 | LED lifespan L70B50 [h]: | 132000 |
| Luminous flux [lm]: | 5500 | LED lifespan L80B20 [h]: | 84000 |
| Luminous efficacy [lm/W]: | 69 | LED lifespan L90B10 [h]: | 42000 |
| Energy efficiency class: | G | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour temperature [K]: | 3000 | Version: | 4x1 |
| SDCM: | ≤ 3 | Warranty [years]: | 5 |
| Optics: | black HE | CE certificate: | 249/2023 |
| Material of the body: | powder coated steel | Manual: | Download PDF |
| Colour of the body: | black mat | Plik LDT: | Download |
| Dimensions (H/W/T/S) [mm]: | 595/595/36 | | |

TERRA 2 LED N 595X595MM X4 5500LM 830 BLACK MAT STRUCTURE (72W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 999543 | Plasterboard recessing kit 630x630 white (steel version) |
| 374845 | Frame adapter KG 635x635 WHITE |
| 998966 | Frame steel white structure RAL9016 600x600 SM "well effect" |



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 249/2023