

TERRA 2 LED N 595X595MM X4 5900LM 840 BLACK MAT STRUCTURE (72W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	239557
Ingress protection:	IP20
Nominal power [W]:	72
Luminous flux [lm]*:	5900
SDCM:	≤ 3
Material of the body:	powder coated steel
Optics:	black HE
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	595/595/36

CHARACTERISTICS

Recessed square LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter), or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

UGR <19

Unified Glare Rating is an indicator characterizing glare. The lower the Unified Lighting Rating Index (UGR), the lower the glare. In the case of luminaires designed for office spaces, UGR <19, among others improves the comfort of work, reduces errors and fatigue. The UGR value also depends on many factors characterizing the room and the location of the observer. Special computer programs should be used to precisely determine the degree of glare for specific conditions.

APPLICATION

General-purpose recessed luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

TERRA 2 LED N 595X595MM X4 5900LM 840 BLACK MAT STRUCTURE (72W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	239557	Dimensions (H/W/T/S) [mm]:	595/595/36
Light source:	LED module	Ingress protection:	IP20
Nominal power [W]:	72	Mounting version:	surface
Rated power of the luminaire [W]:	79.70	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Category type:	louvres
Luminous flux [lm]:	5900	LED lifespan L70B50 [h]:	132000
Luminous efficacy [lm/W]:	74	LED lifespan L80B20 [h]:	84000
Energy efficiency class:	F	LED lifespan L90B10 [h]:	42000
Colour temperature [K]:	4000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	≤ 3	Version:	4x1
Optics:	black HE	Warranty [years]:	5
Material of the body:	powder coated steel	CE certificate:	249/2023
Colour of the body:	black mat	Manual:	Download PDF

TERRA 2 LED N 595X595MM X4 5900LM 840 BLACK MAT STRUCTURE (72W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 19 June 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 249/2023