DETAILED CARD



TECHNICAL PARAMETERS

Index: 239304

Ingress protection: IP20

Nominal power [W]: 36

Luminous flux [lm]*: 3950

Color rendering index (Ra) >: 80

SDCM:

Material of the body: powder coated steel

Optics: HE

Mounting version: recessed

Dimensions (H/W/T/S) [mm]: 595/595/32

CHARACTERISTICS

Recessed square LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter), or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum. UGR <19

Unified Glare Rating is an indicator characterizing glare. The lower the Unified Lighting Rating Index (UGR), the lower the glare. In the case of luminaires designed for office spaces, UGR <19, among, others improves the comfort of work, reduces errors and fatigue. The UGR value also depends on many factors characterizing the room and the location of the observer. Special computer programs should be used to precisely determine the degree of glare for specific conditions.

APPLICATION

General-purpose recessed luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.




DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	239304
Light source:	LED module
Nominal power [W]:	36
Rated power of the luminaire [W]:	39.80
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	3950
Luminous efficacy [lm/W]:	99
Energy efficiency class:	Е
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.96
Optics:	HE
Material of the body:	powder coated steel

Colour of the body:	white gloss	
Dimensions (H/W/T/S) [mm]:	595/595/32	
Ingress protection:	IP20	
Mounting version:	recessed	
Working temperature [°C]:	from -20 to +35	
Category type:	troffers	
LED lifespan L70B50 [h]:	132000	
LED lifespan L80B20 [h]:	84000	
LED lifespan L90B10 [h]:	42000	
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)	
Version:	2x1	
Warranty [years]:	5	
CE certificate:	248/2023	
Manual:	Download PDF	
Plik LDT:	Download	

LIGHT CURVES



DETAILED CARD

TECHNICAL DETAILS




TERRA 2 LED





DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"







Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

