TERRA 2 LED ZW 595X595MM X2 5050LM 830 WHITE MAT (48W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	239472
--------	--------

Ingress protection: IP20

Nominal power [W]: 48

Luminous flux [lm]*: 5050

Color rendering index (Ra) >: 80

SDCM: 3

Material of the body: powder coated steel

Optics: HE

Mounting version: suspended

Dimensions (H/W/T/S) [mm]: 595/595/38

CHARACTERISTICS

Recessed square LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter), or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum. UGR <19

Unified Glare Rating is an indicator characterizing glare. The lower the Unified Lighting Rating Index (UGR), the lower the glare. In the case of luminaires designed for office spaces, UGR <19, among, others improves the comfort of work, reduces errors and fatigue. The UGR value also depends on many factors characterizing the room and the location of the observer. Special computer programs should be used to precisely determine the degree of glare for specific conditions.

APPLICATION

General-purpose recessed luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.



TERRA 2 LED ZW 595X595MM X2 5050LM 830 WHITE MAT (48W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	239472
Light source:	LED module
Nominal power [W]:	48
Rated power of the luminaire [W]:	53.40
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	5050
Luminous efficacy [lm/W]:	95
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.97
Optics:	HE
Material of the body:	powder coated steel

Colour of the body:	white mat
Dimensions (H/W/T/S) [mm]:	595/595/38
Ingress protection:	IP20
Mounting version:	suspended
Working temperature [°C]:	from -20 to +35
Category type:	troffers
LED lifespan L70B50 [h]:	132000
LED lifespan L80B20 [h]:	84000
LED lifespan L90B10 [h]:	42000
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Version:	2x1
Warranty [years]:	5
CE certificate:	249/2023
Manual:	Download PDF
Plik LDT:	Download





TERRA 2 LED ZW 595X595MM X2 5050LM 830 WHITE MAT (48W)


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"







Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

