

TERRA 2 LED ZW 595X595MM X4 5900LM 840 BLACK MAT STRUCTURE (72W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	239700
Ingress protection:	IP20
Nominal power [W]:	72
Luminous flux [lm]*:	5900
SDCM:	≤ 3
Material of the body:	powder coated steel
Optics:	black HE
Mounting version:	suspended
Dimensions (H/W/T/S) [mm]:	595/595/38

CHARACTERISTICS

Recessed square LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter), or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

UGR <19

Unified Glare Rating is an indicator characterizing glare. The lower the Unified Lighting Rating Index (UGR), the lower the glare. In the case of luminaires designed for office spaces, UGR <19, among, others improves the comfort of work, reduces errors and fatigue. The UGR value also depends on many factors characterizing the room and the location of the observer. Special computer programs should be used to precisely determine the degree of glare for specific conditions.

APPLICATION

General-purpose recessed luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

TERRA 2 LED ZW 595X595MM X4 5900LM 840 BLACK MAT STRUCTURE (72W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	239700	Ingress protection:	IP20
Light source:	LED module	Mounting version:	suspended
Nominal power [W]:	72	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	79.70	Category type:	troffers
Supply voltage [V]:	220-240	LED lifespan L70B50 [h]:	132000
Luminous flux [lm]:	5900	LED lifespan L80B20 [h]:	84000
Luminous efficacy [lm/W]:	74	LED lifespan L90B10 [h]:	42000
Energy efficiency class:	F	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour temperature [K]:	4000	Version:	4x1
SDCM:	≤ 3	Warranty [years]:	5
Optics:	black HE	CE certificate:	249/2023
Material of the body:	powder coated steel	Manual:	Download PDF
Colour of the body:	black mat	Plik LDT:	Download
Dimensions (H/W/T/S) [mm]:	595/595/38		

TERRA 2 LED ZW 595X595MM X4 5900LM 840 BLACK MAT STRUCTURE (72W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)