

# TERRA 2 LED N 1195X230MM X2 4750LM 840 WHITE GLOSSY (41W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	237904
<b>Ingress protection:</b>	IP20
<b>Nominal power [W]:</b>	41
<b>Luminous flux [lm]*:</b>	4750
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Material of the body:</b>	powder coated steel
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	1195/230/36
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter) or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

## APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

# TERRA 2 LED N 1195X230MM X2 4750LM 840 WHITE GLOSSY (41W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	41	SDCM:	≤ 3
Index:	237904	Power factor:	0.97
Colour temperature [K]:	4000	Material of the body:	powder coated steel
Light source:	LED module	Ingress protection:	IP20
Luminous flux [lm]:	4750	Mounting version:	surface
Optics:	HE	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	44.80	Category type:	louvres
Version:	2x1	Category of application:	commercial facilities, educational institutions
Supply voltage [V]:	220-240	LED lifespan L70B50 [h]:	132000
Colour of the body:	white gloss	LED lifespan L80B20 [h]:	84000
Frequency [Hz]:	50 - 60	LED lifespan L90B10 [h]:	42000
Dimensions (H/W/T/S) [mm]:	1195/230/36	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Luminous efficacy [lm/W]:	99	Warranty [years]:	5
Energy efficiency class:	E	CE certificate:	<a href="#">354/2023</a>
Electrical protection class:	II	Manual:	<a href="#">Download PDF</a>
Colour rendering index:	>80	Plik LDT:	<a href="#">Pobierz</a>

Card creation date: 31 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023