


# TERRA 2 LED N 595X300MM X2 3700LM 830 BLACK MAT STRUCTURE (48W)

DETAILED CARD



## TECHNICAL PARAMETERS

|   |                     |
|---|---------------------|
| <b>Index:</b>                           | 237546              |
| <b>Ingress protection:</b>              | IP20                |
| <b>Nominal power [W]:</b>               | 48                  |
| <b>Luminous flux [lm]*:</b>             | 3700                |
| <b>Color rendering index (Ra) &gt;:</b> | 80                  |
| <b>SDCM:</b>                            | 3                   |
| <b>Material of the body:</b>            | powder coated steel |
| <b>Mounting version:</b>                | surface             |
| <b>Dimensions (H/W/T/S) [mm]:</b>       | 595/300/36          |
| <b>Warranty [years]:</b>                | 5                   |

## CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter) or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

## APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

# TERRA 2 LED N 595X300MM X2 3700LM 830 BLACK MAT STRUCTURE (48W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|  |                     |                                   |   |
|--|---------------------|-----------------------------------|---|
| <b>Index:</b>                            | 237546              | <b>Colour of the body:</b>        | black mat   |
| <b>Light source:</b>                     | LED module          | <b>Dimensions (H/W/T/S) [mm]:</b> | 595/300/36  |
| <b>Nominal power [W]:</b>                | 48                  | <b>Ingress protection:</b>        | IP20  |
| <b>Rated power of the luminaire [W]:</b> | 53.40               | <b>Mounting version:</b>          | surface   |
| <b>Supply voltage [V]:</b>               | 220-240             | <b>Working temperature [°C]:</b>  | from -20 to +35   |
| <b>Frequency [Hz]:</b>                   | 50 - 60             | <b>Category type:</b>             | troffers  |
| <b>Luminous flux [lm]:</b>               | 3700                | <b>Category of application:</b>   | educational institutions,<br>commercial facilities                                |
| <b>Luminous efficacy [lm/W]:</b>         | 69                  | <b>Version:</b>                   | 2x1   |
| <b>Energy efficiency class:</b>          | G                   | <b>LED lifespan L70B50 [h]:</b>   | 132000  |
| <b>Electrical protection class:</b>      | II                  | <b>LED lifespan L80B10 [h]:</b>   | 84000   |
| <b>Colour temperature [K]:</b>           | 3000                | <b>LED lifespan L90B10 [h]:</b>   | 42000   |
| <b>Color rendering index (Ra) &gt;:</b>  | 80                  | <b>Photobiological safety:</b>    | Risk Group 1 (no photobiological<br>hazard under normal behavioral<br>limitation) |
| <b>SDCM:</b>                             | 3                   | <b>Warranty [years]:</b>          | 5   |
| <b>Power factor:</b>                     | 0.97                | <b>CE certificate:</b>            | <a href="#">354/2023</a>  |
| <b>Optics:</b>                           | black HE            | <b>Manual:</b>                    | <a href="#">Download PDF</a>  |
| <b>Material of the body:</b>             | powder coated steel | <b>Plik LDT:</b>                  | <a href="#">Download</a>  |

Card creation date: 28 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023