

# TERRA 2 LED ZW 1195X230MM X2 2600LM 840 WHITE GLOSSY (20W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                   |                     |
|-----------------------------------|---------------------|
| <b>Index:</b>                     | 238123              |
| <b>Ingress protection:</b>        | IP20                |
| <b>Nominal power [W]:</b>         | 20                  |
| <b>Luminous flux [lm]*:</b>       | 2600                |
| <b>Colour rendering index:</b>    | >80                 |
| <b>SDCM:</b>                      | ≤ 3                 |
| <b>Material of the body:</b>      | powder coated steel |
| <b>Mounting version:</b>          | suspended           |
| <b>Dimensions (H/W/T/S) [mm]:</b> | 1195/230/38         |
| <b>Warranty [years]:</b>          | 5                   |

## CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface, recessed in modular and suspended. The surface-mounted version uses solutions that enhance the speed and safety of installation. A multitude of versions & dimensions allow to replace worn-out recessed fluorescent luminaires.

## APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

# TERRA 2 LED ZW 1195X230MM X2 2600LM 840 WHITE GLOSSY (20W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |             |                           |   |
|-----------------------------------|-------------|---------------------------|---|
| Nominal power [W]:                | 20          | SDCM:                     | ≤ 3   |
| Index:                            | 238123      | Power factor:             | 0.95  |
| Colour temperature [K]:           | 4000        | Material of the body:     | powder coated steel   |
| Light source:                     | LED module  | Ingress protection:       | IP20  |
| Luminous flux [lm]:               | 2600        | Mounting version:         | suspended   |
| Optics:                           | HE          | Working temperature [°C]: | from -20 to +35   |
| Rated power of the luminaire [W]: | 22.70       | Category type:            | louvres   |
| Version:                          | 2x1         | Category of application:  | commercial facilities, educational institutions                             |
| Supply voltage [V]:               | 220-240     | LED lifespan L70B50 [h]:  | 132000  |
| Colour of the body:               | white gloss | LED lifespan L80B20 [h]:  | 84000   |
| Frequency [Hz]:                   | 50 - 60     | LED lifespan L90B10 [h]:  | 42000   |
| Dimensions (H/W/T/S) [mm]:        | 1195/230/38 | Photobiological safety:   | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Luminous efficacy [lm/W]:         | 115         | Warranty [years]:         | 5   |
| Energy efficiency class:          | E           | CE certificate:           | <a href="#">354/2023</a>  |
| Electrical protection class:      | II          | Manual:                   | <a href="#">Download PDF</a>  |
| Colour rendering index:           | >80         | Plik LDT:                 |   |

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023