

TERRA 2 LED ZW 595X300MM X2 3300LM 830 WHITE MAT (31W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	237683
Ingress protection:	IP20
Nominal power [W]:	31
Luminous flux [lm]*:	3300
Colour rendering index:	80
SDCM:	≤ 3
Material of the body:	powder coated steel
Mounting version:	suspended
Dimensions (H/W/T/S) [mm]:	595/300/38
Warranty [years]:	5

CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter) or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

TERRA 2 LED ZW 595X300MM X2 3300LM 830 WHITE MAT (31W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	237683	Colour of the body:	white mat
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	595/300/38
Nominal power [W]:	31	Ingress protection:	IP20
Rated power of the luminaire [W]:	34.20	Mounting version:	suspended
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Category type:	troffers
Luminous flux [lm]:	3300	Category of application:	educational institutions, commercial facilities
Luminous efficacy [lm/W]:	97	Version:	2x1
Energy efficiency class:	E	LED lifespan L70B50 [h]:	132000
Electrical protection class:	II	LED lifespan L80B20 [h]:	84000
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	42000
Colour rendering index:	80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.95	CE certificate:	354/2023
Optics:	HE	Manual:	Download PDF
Material of the body:	powder coated steel	Plik LDT:	Download

Card creation date: 03 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 354/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl