

# INDUSTRY IP66 LED MR 1450MM 51000LM 840 (318W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	552625
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK08
<b>Nominal power [W]:</b>	318
<b>Luminous flux [lm]*:</b>	51000
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	glass

## CHARACTERISTICS

INDUSTRY IP66 LED MR is a lamp from the NEXT GEN line, which is a new generation of lamps dedicated to LED technology. The body, made from scratch, made of aluminum profile and subjected to anodization process, provides the lamp with strength and solidity, as well as steel sheet ensuring installation stability. LEDs from a reputable manufacturer and new LED modules have an impact on very high luminous efficacy: up to 148 lm / W. This guarantees that the required lighting level is achieved and that significant energy savings are achieved. The shade is made of UV resistant tempered glass. The combination of materials (aluminum and toughened glass) and a non-dismantled construction with an external connector provides the lamp with high resistance to harsh environmental conditions. The design of the lamp allows you to adjust the lighting angle of the two extreme modules, so there is the possibility of precise lighting of selected parts of the object. Suitable for suspended mounting. Options: any RAL color.

## APPLICATION

The multi-purpose LED luminaire has been designed for use in areas requiring high dust and water resistance. It is especially recommended for use in rooms intended for medical and laboratory purposes as well as in industrial premises.


# INDUSTRY IP66 LED MR 1450MM 51000LM 840 (318W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	552625	<b>Impact resistance:</b>	IK08
<b>Light source:</b>	LED module	<b>Ingress protection:</b>	IP66
<b>Nominal power [W]:</b>	318	<b>Mounting version:</b>	suspended
<b>Rated power of the luminaire [W]:</b>	345.90	<b>Working temperature [°C]:</b>	from -15 to +35
<b>Supply voltage [V]:</b>	220-240	<b>Net weight [kg]:</b>	9.900
<b>Frequency [Hz]:</b>	50 - 60	<b>Warranty [years]:</b>	5
<b>Luminous flux [lm]:</b>	51000	<b>Category type:</b>	battens
<b>Luminous efficacy [lm/W]:</b>	148	<b>AC voltage range [V]:</b>	198 - 264
<b>Energy efficiency class:</b>	C	<b>DC voltage range [V]:</b>	176 - 280
<b>Electrical protection class:</b>	I	<b>LED lifespan L70B50 [h]:</b>	108000
<b>Colour temperature [K]:</b>	4000	<b>LED lifespan L80B20 [h]:</b>	71000
<b>Colour rendering index:</b>	>80	<b>LED lifespan L90B10 [h]:</b>	33000
<b>SDCM:</b>	≤ 3	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Diffuser material:</b>	glass	<b>The number of implement units:</b>	3
<b>Material of the body:</b>	aluminium	<b>Warranty [years]:</b>	5
<b>Colour of the body:</b>	grey	<b>CE certificate:</b>	<a href="#">148/2023</a>
<b>Dimensions (H/W/T/S) [mm]:</b>	1450/205/125	<b>Manual:</b>	<a href="#">Download PDF</a>

## TECHNICAL DETAILS



INDUSTRY IP66 LED MR 2

Card creation date: 03 February 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 148/2023