

TYTAN 2 LED 1150MM 9050LM 850 IP66 DALI 55W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	942105
Ingress protection:	IP66
Impact resistance:	IK09
Nominal power [W]:	55
Luminous flux [lm]*:	9050
Colour temperature [K]:	5000
Energy efficiency class:	C
Material of the body:	PC
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

TYTAN 2 LED is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 155 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED module is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

TYTAN 2 LED 1150MM 9050LM 850 IP66 DALI 55W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	55	Colour of the body:	grey
Index:	942105	Mounting dimensions [mm]:	800
EAN:	5905963942105	Impact resistance:	IK09
Colour temperature [K]:	5000	Ingress protection:	IP66
Light source:	LED module	Mounting version:	surface, suspended
Luminous flux [lm]:	9050	Working temperature [°C]:	from -20 to +35
Diffuser type:	MAT	Net weight [kg]:	1.500
Rated power of the luminaire [W]:	59.30	Mark D:	1
Supply voltage [V]:	220-240	Category type:	battens
DIMM DALI:	1	Category of application:	industrial
Frequency [Hz]:	50 - 60	AC voltage range [V]:	220 - 240
Luminous efficacy [lm/W]:	153	LED lifespan L70B50 [h]:	109000
Dimensions (H/W/T/S) [mm]:	1152/85/80	LED lifespan L80B20 [h]:	69000
Energy efficiency class:	C	LED lifespan L90B10 [h]:	34000
Electrical protection class:	I	ETIM class:	ECO00109
Colour rendering index:	>80	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.95	CE certificate:	127/2023
Exchangeable source:	1	PZH certificate:	B-BK-60212-0152/20
Diffuser material:	PC	HACCP:	852/2004
Material of the body:	PC	Manual:	Download PDF
		ENEC Certificate:	0310/ENEC/23
		Plik LDT:	Pobierz

TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor



wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

TYTAN 2 LED 1150MM 9050LM 850 IP66 DALI 55W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
941375	TYTAN 2 LED 1150mm 2650lm 840 - lighting module
941382	TYTAN 2 LED 1150mm 4550lm 840 - lighting module
941405	TYTAN 2 LED 1450mm 5650lm 840 - lighting module
941412	TYTAN 2 LED 1450mm 7050lm 840 - lighting module
941429	TYTAN 2 LED 1450mm 11300lm 840 - lighting module
941856	TYTAN 2 LED 1150mm 2450lm 830 - lighting module
941863	TYTAN 2 LED 1150mm 4150lm 830 - lighting module
941870	TYTAN 2 LED 1150mm 7300/8400lm 830 - lighting module
941887	TYTAN 2 LED 1450mm 5250lm 830 - lighting module
941894	TYTAN 2 LED 1450mm 6550lm 830 - lighting module
941900	TYTAN 2 LED 1450mm 10500lm 830 - lighting module
942358	TYTAN 2 LED 1150mm 2650lm 850 - lighting module
942365	TYTAN 2 LED 1150mm 4550lm 850 - lighting module
942372	TYTAN 2 LED 1150mm 7850/9050lm 850 - lighting module
942389	TYTAN 2 LED 1450mm 5650lm 850 - lighting module
942396	TYTAN 2 LED 1450mm 7050lm 850 - lighting module
942402	TYTAN 2 LED 1450mm 11300lm 850 - lighting module



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 127/2023