

# TYTAN 2 LED CHEMO 1150MM 4450LM 840 IP66 DALI 28W

## DETAILED CARD



### TECHNICAL PARAMETERS

Index:	942549
Ingress protection:	IP66
Impact resistance:	IK09
Nominal power [W]:	28
Luminous flux [lm]*:	4550
Colour temperature [K]:	4000
Material of the body:	ABS
Colour of the body:	grey
Diffuser material:	PCT-G
Diffuser type:	matt

### CHARACTERISTICS

TYTAN 2 LED CHEMO is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 155 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED module is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). Motion sensor mounting height: up to 5 meters.

Diffuser of the luminaire is made of copolyester (PCT-G), characterised by higher resistance to chemicals like, for example, ammonia and chemical disinfectants. As a result, it can be used in a tough chemical environment without any cracks, misting or scratches.

The material of the diffuser is GREENGUARD certified, thus ensuring that the luminaires for indoor use meet strict chemical emission limits, and contributing to healthier indoor environments.

### APPLICATION

The multifunction LED lighting fixture is designed for use in areas with high requirements regarding dust tightness and water tightness. Especially recommended for:

- buildings where breeding animals are kept;
- medical rooms where chemical disinfectants are used.

# TYTAN 2 LED CHEMO 1150MM 4450LM 840 IP66 DALI 28W

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE


Index:	942549	Impact resistance:	IK09
EAN:	5905963942549	Ingress protection:	IP66
Light source:	LED module	Mounting version:	surface, suspended
Nominal power [W]:	28	Working temperature [°C]:	from -20 to +40
Rated power of the luminaire [W]:	29.75	DIMM DALI:	yes
Supply voltage [V]:	220-240	Net weight [kg]:	1.500
Frequency [Hz]:	50 - 60	Mark D:	yes
Luminous flux [lm]:	4550	Category type:	battens
Luminous efficacy [lm/W]:	153	Category of application:	industrial
Energy efficiency class:	C	AC voltage range [V]:	220 - 240
Electrical protection class:	I	LED lifespan L70B50 [h]:	109000
Colour temperature [K]:	4000	LED lifespan L80B20 [h]:	69000
Colour rendering index:	80	LED lifespan L90B10 [h]:	34000
SDCM:	≤ 3	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Power factor:	0.92	Warranty [years]:	5
Exchangeable source:	yes	CE certificate:	<a href="#">132/2023</a>
Diffuser material:	PCT-G	HACCP:	<a href="#">852/2004</a>
Diffuser type:	matt	Warranty [years]:	5
Material of the body:	ABS	Manual:	<a href="#">Download PDF</a>
Colour of the body:	grey	ENEC Certificate:	<a href="#">0310/ENEC/23</a>
Dimensions (H/W/T/S) [mm]:	1152/85/80	PZH certificate:	<a href="#">B-BK-60212-0152/20</a>
Mounting dimensions [mm]:	800	Plik LDT:	<a href="#">Download</a>

# TYTAN 2 LED CHEMA 1150MM 4450LM 840 IP66 DALI 28W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
80000279	Gland. beam, Codar, soft polyvinyl chloride (PVC-P), gray



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 132/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl