

# TYTAN 2 LED CHEMO 1450MM 11300LM 840 IP66 LS2 69W

DETAILED CARD



## TECHNICAL PARAMETERS

|                                |        |
|--------------------------------|--------|
| <b>Index:</b>                  | 942617 |
| <b>Ingress protection:</b>     | IP66   |
| <b>Impact resistance:</b>      | IK09   |
| <b>Nominal power [W]:</b>      | 69     |
| <b>Luminous flux [lm]*:</b>    | 11300  |
| <b>Colour temperature [K]:</b> | 4000   |
| <b>Material of the body:</b>   | ABS    |
| <b>Colour of the body:</b>     | grey   |
| <b>Diffuser material:</b>      | PCT-G  |
| <b>Diffuser type:</b>          | MAT    |

## CHARACTERISTICS

TYTAN 2 LED CHEMO is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 155 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED module is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). Motion sensor mounting height: up to 5 meters. Diffuser of the luminaire is made of copolyester (PCT-G), characterised by higher resistance to chemicals like, for example, ammonia and chemical disinfectants. As a result, it can be used in a tough chemical environment without any cracks, misting or scratches. The material of the diffuser is GREENGUARD certified, thus ensuring that the luminaires for indoor use meet strict chemical emission limits, and contributing to healthier indoor environments.

## APPLICATION

The multifunction LED lighting fixture is designed for use in areas with high requirements regarding dust tightness and water tightness. Especially recommended for:

- buildings where breeding animals are kept;
- medical rooms where chemical disinfectants are used.

# TYTAN 2 LED CHEMO 1450MM 11300LM 840 IP66 LS2 69W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|  |               |                                  |   |
|--|---------------|----------------------------------|---|
| <b>Index:</b>                            | 942617        | <b>Impact resistance:</b>        | IK09  |
| <b>EAN:</b>                              | 5905963942617 | <b>Ingress protection:</b>       | IP66  |
| <b>Light source:</b>                     | LED module    | <b>Mounting version:</b>         | surface, suspended  |
| <b>Nominal power [W]:</b>                | 69            | <b>Working temperature [°C]:</b> | from -20 to +35   |
| <b>Rated power of the luminaire [W]:</b> | 74.37         | <b>Wire type:</b>                | 5x1,5   |
| <b>Supply voltage [V]:</b>               | 220-240       | <b>Through wiring:</b>           | LS2   |
| <b>Frequency [Hz]:</b>                   | 50 - 60       | <b>Net weight [kg]:</b>          | 2.280   |
| <b>Luminous flux [lm]:</b>               | 11300         | <b>Mark D:</b>                   | yes   |
| <b>Luminous efficacy [lm/W]:</b>         | 152           | <b>Category type:</b>            | battens   |
| <b>Energy efficiency class:</b>          | C             | <b>Category of application:</b>  | industrial  |
| <b>Electrical protection class:</b>      | I             | <b>AC voltage range [V]:</b>     | 220 - 240   |
| <b>Colour temperature [K]:</b>           | 4000          | <b>LED lifespan L70B50 [h]:</b>  | 109000  |
| <b>Colour rendering index:</b>           | >80           | <b>LED lifespan L80B20 [h]:</b>  | 69000   |
| <b>SDCM:</b>                             | ≤ 3           | <b>LED lifespan L90B10 [h]:</b>  | 34000   |
| <b>Power factor:</b>                     | 0.97          | <b>Photobiological safety:</b>   | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| <b>Exchangeable source:</b>              | yes           | <b>Warranty [years]:</b>         | 5   |
| <b>Diffuser material:</b>                | PCT-G         | <b>CE certificate:</b>           | <a href="#">132/2023</a>  |
| <b>Diffuser type:</b>                    | MAT           | <b>HACCP:</b>                    | <a href="#">852/2004</a>  |
| <b>Material of the body:</b>             | ABS           | <b>Warranty [years]:</b>         | 5   |
| <b>Colour of the body:</b>               | grey          | <b>Manual:</b>                   | <a href="#">Download PDF</a>  |
| <b>Dimensions (H/W/T/S) [mm]:</b>        | 1432/85/80    | <b>ENEC Certificate:</b>         | <a href="#">0310/ENEC/23</a>  |
| <b>Mounting dimensions [mm]:</b>         | 970           | <b>PZH certificate:</b>          | <a href="#">B-BK-60212-0152/20</a>  |

# TYTAN 2 LED CHEMO 1450MM 11300LM 840 IP66 LS2 69W

DETAILED CARD

## ACCESSORIES AVAILABLE

| index    | Name  |
|----------|---|
| 60000006 | M16 stuffing box plug various PA black M-16 - BPM-21      |
| 908231   | TYTAN LED - holder  |
| 80000279 | Gland. beam, Codar, soft polyvinyl chloride (PVC-P), gray |



M16 stuffing box plug various PA black  
M-16 - BPM-21 (60000006)

Card creation date: 13 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 132/2023