


TERRA 2 LED N TAB 1160X120MM 15ST 4200LM 840 WHITE GLOSSY (36W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	226335
Ingress protection:	IP20
Nominal power [W]:	36
Luminous flux [lm]*:	4200
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel
Optics:	HE
Mounting version:	surface

CHARACTERISTICS

A luminaire equipped with energy-efficient LED modules characterised by a high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare. The surface-mounted version features solutions for fast and safe installation. The asymmetric version is used to illuminate school and academic blackboards, paintings and other objects on walls.

APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration. The asymmetric version is used to illuminate school and academic tables, paintings and other objects on the walls.


TERRA 2 LED N TAB 1160X120MM 15ST 4200LM 840 WHITE GLOSSY (36W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	226335	Dimensions (H/W/T/S) [mm]:	1160/120/36
Light source:	LED module	Ingress protection:	IP20
Nominal power [W]:	36	Mounting version:	surface
Rated power of the luminaire [W]:	40	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Warranty [years]:	5
Luminous flux [lm]:	4200	CE certificate:	354/2023
Luminous efficacy [lm/W]:	106	Category type:	louvres
Energy efficiency class:	E	Category of application:	commercial facilities, educational institutions
Electrical protection class:	II	Version:	asymmetric
Colour temperature [K]:	4000	AC voltage range [V]:	220 - 240
Colour rendering index:	>80	LED lifespan L70B50 [h]:	132000
SDCM:	≤ 3	LED lifespan L80B20 [h]:	84000
Power factor:	0.96	LED lifespan L90B10 [h]:	42000
Optics:	HE	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	powder coated steel	Warranty [years]:	5
Colour of the body:	white gloss	Manual:	Download PDF

LIGHT CURVES



Card creation date: 27 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl