## TERRA 2 LED N TAB 1160X120MM 15ST 4200LM 840 WHITE GLOSSY (36W)

**DETAILED CARD** 





**Index:** 226335

Ingress protection: IP20

Nominal power [W]: 36

Luminous flux [lm]\*: 4200

Colour rendering index: 80

**SDCM**: 3

Energy efficiency class:

Material of the body: powder coated steel

Optics: HE

Mounting version: surface

## **CHARACTERISTICS**

A luminaire equipped with energy-efficient LED modules characterised by a high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare. The surface-mounted version features solutions for fast and safe installation. The asymmetric version is used to illuminate school and academic blackboards, paintings and other objects on walls.

### **APPLICATION**

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration. The asymmetric version is used to illuminate school and academic tables, paintings and other objects on the walls.



# TERRA 2 LED N TAB 1160X120MM 15ST 4200LM 840 WHITE GLOSSY (36W)


**DETAILED CARD** 

## **TECHNICAL PARAMETERS TABLE**

Index:	226335
Light source:	LED module
Nominal power [W]:	36
Rated power of the luminaire [W]:	40
Supply voltage [V]:	220-240
Luminous flux [lm]:	4200
Luminous efficacy [lm/W]:	106
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	3
Power factor:	0.96
Optics:	HE
Material of the body:	powder coated steel
Colour of the body:	white gloss
Dimensions (H/W/T/S) [mm]:	1160/120/36

Ingress protection:	IP20
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Warranty [years]:	5
CE certificate:	<u>354/2023</u>
Category type:	troffers
Category of application:	educational institutions, commercial facilities
Version:	asymmetric
AC voltage range [V]:	220 - 240
LED lifespan L70B50 [h]:	132000
LED lifespan L80B20 [h]:	84000
LED lifespan L90B10 [h]:	42000
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
Manual:	Download PDF
Plik LDT:	Download

## **LIGHT CURVES**



Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

