

TERRA 2 LED LONG N X2 1195X140MM 3500LM 840 WHITE GLOSSY (31W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-----------------------------------|---------------------|
| Index: | 226373 |
| Ingress protection: | IP20 |
| Nominal power [W]: | 31 |
| Luminous flux [lm]*: | 3500 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Material of the body: | powder coated steel |
| Mounting version: | surface |
| Dimensions (H/W/T/S) [mm]: | 1195/140/36 |
| Warranty [years]: | 5 |

CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter) or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

TERRA 2 LED LONG N X2 1195X140MM 3500LM 840 WHITE GLOSSY (31W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------------|-----------------------------------|---|
| Index: | 226373 | Dimensions (H/W/T/S) [mm]: | 1195/140/36 |
| Light source: | LED module | Ingress protection: | IP20 |
| Nominal power [W]: | 31 | Mounting version: | surface |
| Rated power of the luminaire [W]: | 34 | Working temperature [°C]: | from -20 to +35 |
| Supply voltage [V]: | 220-240 | Category type: | louvres |
| Luminous flux [lm]: | 3500 | Category of application: | commercial facilities, educational institutions |
| Luminous efficacy [lm/W]: | 102 | Version: | 2x1 |
| Energy efficiency class: | E | AC voltage range [V]: | 220 - 240 |
| Electrical protection class: | II | UGR (4H8H): | <16,7 |
| Colour temperature [K]: | 4000 | LED lifespan L70B50 [h]: | 132000 |
| Colour rendering index: | >80 | LED lifespan L80B20 [h]: | 84000 |
| SDCM: | ≤ 3 | LED lifespan L90B10 [h]: | 42000 |
| Power factor: | 0.95 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Optics: | HE | Warranty [years]: | 5 |
| Material of the body: | powder coated steel | CE certificate: | 354/2023 |
| Colour of the body: | white gloss | Manual: | Download PDF |

Card creation date: 31 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023