


# TERRA 2 LED LONG N X2 1195X140MM 5400LM 840 WHITE GLOSSY (48W)

DETAILED CARD



## TECHNICAL PARAMETERS

|   |                     |
|---|---------------------|
| <b>Index:</b>                           | 226410              |
| <b>Ingress protection:</b>              | IP20                |
| <b>Nominal power [W]:</b>               | 48                  |
| <b>Luminous flux [lm]*:</b>             | 5400                |
| <b>Color rendering index (Ra) &gt;:</b> | 80                  |
| <b>SDCM:</b>                            | 3                   |
| <b>Material of the body:</b>            | powder coated steel |
| <b>Mounting version:</b>                | surface             |
| <b>Dimensions (H/W/T/S) [mm]:</b>       | 1195/140/36         |
| <b>Warranty [years]:</b>                | 5                   |

## CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter) or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

## APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

# TERRA 2 LED LONG N X2 1195X140MM 5400LM 840 WHITE GLOSSY (48W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|  |                     |                                  |   |
|--|---------------------|----------------------------------|---|
| <b>Index:</b>                            | 226410              | <b>Ingress protection:</b>       | IP20  |
| <b>Light source:</b>                     | LED module          | <b>Mounting version:</b>         | surface   |
| <b>Nominal power [W]:</b>                | 48                  | <b>Working temperature [°C]:</b> | from -20 to +35   |
| <b>Rated power of the luminaire [W]:</b> | 53                  | <b>Category type:</b>            | troffers  |
| <b>Supply voltage [V]:</b>               | 220-240             | <b>Category of application:</b>  | educational institutions,<br>commercial facilities                                |
| <b>Luminous flux [lm]:</b>               | 5400                | <b>Version:</b>                  | 2x1   |
| <b>Luminous efficacy [lm/W]:</b>         | 101                 | <b>AC voltage range [V]:</b>     | 220 - 240   |
| <b>Energy efficiency class:</b>          | E                   | <b>UGR (4H8H):</b>               | <16,7   |
| <b>Electrical protection class:</b>      | II                  | <b>LED lifespan L70B50 [h]:</b>  | 132000  |
| <b>Colour temperature [K]:</b>           | 4000                | <b>LED lifespan L80B10 [h]:</b>  | 84000   |
| <b>Color rendering index (Ra) &gt;:</b>  | 80                  | <b>LED lifespan L90B10 [h]:</b>  | 42000   |
| <b>SDCM:</b>                             | 3                   | <b>Photobiological safety:</b>   | Risk Group 1 (no photobiological<br>hazard under normal behavioral<br>limitation) |
| <b>Power factor:</b>                     | 0.97                | <b>Warranty [years]:</b>         | 5   |
| <b>Optics:</b>                           | HE                  | <b>CE certificate:</b>           | <a href="#">354/2023</a>  |
| <b>Material of the body:</b>             | powder coated steel | <b>Manual:</b>                   | <a href="#">Download PDF</a>  |
| <b>Colour of the body:</b>               | white gloss         | <b>Pliik LDT:</b>                | <a href="#">Download</a>  |
| <b>Dimensions (H/W/T/S) [mm]:</b>        | 1195/140/36         |                                  |   |

Card creation date: 28 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023