

# TERRA 2 LED LONG N X4 1195X170MM 7000LM 840 WHITE MAT (62W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	226427
<b>Ingress protection:</b>	IP20
<b>Nominal power [W]:</b>	62
<b>Luminous flux [lm]*:</b>	7000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Material of the body:</b>	powder coated steel
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	1195/170/36
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter) or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

## APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.


# TERRA 2 LED LONG N X4 1195X170MM 7000LM 840 WHITE MAT (62W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	62	Mounting version:	surface
Index:	226427	Working temperature [°C]:	from -20 to +35
Colour temperature [K]:	4000	Category type:	louvres
Light source:	LED module	Category of application:	commercial facilities, educational institutions
Luminous flux [lm]:	7000	AC voltage range [V]:	220 - 240
Optics:	HE	UGR (4H8H):	< 16.7
Rated power of the luminaire [W]:	68	LED lifespan L70B50 [h]:	132000
Version:	2x2	LED lifespan L80B20 [h]:	84000
Supply voltage [V]:	220 - 240	LED lifespan L90B10 [h]:	42000
Colour of the body:	white mat	Optics material:	black HE
Dimensions (H/W/T/S) [mm]:	1195/170/36	Ring material:	biały mat
Luminous efficacy [lm/W]:	102	Mounting dimensions [mm]:	1195/170/36
Energy efficiency class:	E	DC voltage range [V]:	220 - 240
Electrical protection class:	II	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	<a href="#">354/2023</a>
Power factor:	0.95	Manual:	<a href="#">Download PDF</a>
Material of the body:	powder coated steel	Impact resistance:	IK03
Ingress protection:	IP20	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl