

SITE LITE FUTURE LED 3500LM 840 220-240V IP44 I 5M DK SOCKET DK GREY (26W) MAGNET

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------|--------|
| Index: | 621215 |
| Ingress protection: | IP44 |
| Impact resistance: | IK10 |
| Nominal power [W]: | 26 |
| Colour temperature [K]: | 4000 |
| Luminous flux [lm]*: | 3500 |
| Energy efficiency class: | D |
| Electrical protection class: | I |
| Material of the body: | PP |
| Diffuser material: | PC |

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets
- with a magnet in the base

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 3500LM 840 220-240V IP44 I 5M DK SOCKET DK GREY (26W) MAGNET

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-------------------------------------|------------------------------------|-----------------------------------|------------------------------|
| Index: | 621215 | Material of the body: | PP |
| Category type: | general construction site lighting | Colour of the body: | graphite |
| Light source: | LED module | Dimensions (H/W/T/S) [mm]: | ø198/154 |
| Nominal power [W]: | 26 | Impact resistance: | IK10 |
| Luminous flux [lm]: | 3500 | Ingress protection: | IP44 |
| Supply voltage [V]: | 220-240 | Plug type: | DK |
| Luminous efficacy [lm/W]: | 158 | Socket type: | DK |
| Energy efficiency class: | D | Sockets: | 1 |
| Electrical protection class: | I | Cable length [m]: | 5 |
| Colour temperature [K]: | 4000 | Magnet: | yes |
| Diffuser material: | PC | Net weight [kg]: | 1.400 |
| Diffuser type: | milky | Manual: | Download PDF |

Card creation date: 30 June 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 271/2023