

# SITE LITE FUTURE LED 3500LM 840 220-240V IP44 I 5M UNI-SCHUKO SOCKET PL-FR GREY (26W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |        |
|-------------------------------------|--------|
| <b>Index:</b>                       | 621093 |
| <b>Ingress protection:</b>          | IP54   |
| <b>Impact resistance:</b>           | IK10   |
| <b>Nominal power [W]:</b>           | 26     |
| <b>Colour temperature [K]:</b>      | 4000   |
| <b>Luminous flux [lm]*:</b>         | 3500   |
| <b>Energy efficiency class:</b>     | D      |
| <b>Electrical protection class:</b> | I      |
| <b>Material of the body:</b>        | PP     |
| <b>Diffuser material:</b>           | PC     |

## CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets
- with a magnet in the base

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# SITE LITE FUTURE LED 3500LM 840 220-240V IP44 I 5M UNI-SCHUKO SOCKET PL-FR GREY (26W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                     |                                    |                                   |                              |
|-------------------------------------|------------------------------------|-----------------------------------|------------------------------|
| <b>Index:</b>                       | 621093                             | <b>Material of the body:</b>      | PP                           |
| <b>Category type:</b>               | general construction site lighting | <b>Colour of the body:</b>        | graphite                     |
| <b>Light source:</b>                | LED module                         | <b>Dimensions (H/W/T/S) [mm]:</b> | ø198/154                     |
| <b>Nominal power [W]:</b>           | 26                                 | <b>Impact resistance:</b>         | IK10                         |
| <b>Luminous flux [lm]:</b>          | 3500                               | <b>Ingress protection:</b>        | IP54                         |
| <b>Supply voltage [V]:</b>          | 220-240                            | <b>Plug type:</b>                 | UNI-SCHUKO                   |
| <b>Luminous efficacy [lm/W]:</b>    | 158                                | <b>Socket type:</b>               | PL-FR                        |
| <b>Energy efficiency class:</b>     | D                                  | <b>Sockets:</b>                   | 1                            |
| <b>Electrical protection class:</b> | I                                  | <b>Cable length [m]:</b>          | 5                            |
| <b>Colour temperature [K]:</b>      | 4000                               | <b>Net weight [kg]:</b>           | 1.400                        |
| <b>Diffuser material:</b>           | PC                                 | <b>Manual:</b>                    | <a href="#">Download PDF</a> |
| <b>Diffuser type:</b>               | milky                              |                                   |                              |

Card creation date: 30 June 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 271/2023