SITE LITE FUTURE LED 3500LM 840 220-240V IP44 I 5M UNI-SCHUKO SOCKET PL-FR GREY (26W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621093
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	26
Colour temperature [K]:	4000
Luminous flux [lm]*:	3500
Energy efficiency class:	D
Electrical protection class:	I
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.
The variety of available versions ensures optimal adjustment to your needs.

Available versions:
• with sockets: PL-FR, DK, SCHUCKO
• without sockets
• with a magnet in the base

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 3500LM 840 220-240V IP44 I 5M UNI-SCHUKO SOCKET PL-FR GREY (26W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621093	**Material of the body:**	PP
Category type:	general construction site lighting	**Colour of the body:**	graphite
Light source:	LED module	**Dimensions (H/W/T/S) [mm]:**	ø198/154
Nominal power [W]:	26	**Impact resistance:**	IK10
Luminous flux [lm]:	3500	**Ingress protection:**	IP54
Supply voltage [V]:	220-240	**Plug type:**	UNI-SCHUKO
Luminous efficacy [lm/W]:	158	**Socket type:**	PL-FR
Energy efficiency class:	D	**Sockets:**	1
Electrical protection class:	I	**Cable length [m]:**	5
Colour temperature [K]:	4000	**Net weight [kg]:**	1.400
Diffuser material:	PC	**Manual:**	Download PDF
Diffuser type:	milky		

Card creation date: 30 June 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 271/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl