

SITE LITE FUTURE LED 3500LM 850 220-240V IP44 I 5M UNI-SCHUKO SOCKET SCHUCKO GREY (26W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621352
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	26
Colour temperature [K]:	5000
Luminous flux [lm]*:	3500
Energy efficiency class:	D
Electrical protection class:	I
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

- Available versions:
- with sockets: PL-FR, DK, SCHUCKO
 - without sockets
 - with a magnet in the base

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 3500LM 850 220-240V IP44 I 5M

UNI-SCHUKO SOCKET SCHUCKO GREY (26W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621352	Material of the body:	PP
Category type:	general construction site lighting	Colour of the body:	graphite
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø198/154
Nominal power [W]:	26	Impact resistance:	IK10
Luminous flux [lm]:	3500	Ingress protection:	IP54
Supply voltage [V]:	220-240	Plug type:	UNI-SCHUKO
Luminous efficacy [lm/W]:	158	Socket type:	SCHUKO
Energy efficiency class:	D	Sockets:	1
Electrical protection class:	I	Cable length [m]:	5
Colour temperature [K]:	5000	Net weight [kg]:	1.400
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	milky		

Card creation date: 30 June 2020
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 271/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl