SITE LITE FUTURE LED 3500LM 850 220-240V IP54 II 5M UNI-SCHUKO GREY (26W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	621345
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	26
Colour temperature [K]:	5000
Luminous flux [lm]*:	3500
Energy efficiency class:	D
Electrical protection class:	II
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Antiglare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets
- · with a magnet in the base

APPLICATION

The luminaire will provide precise illumination of the workplace.



SITE LITE FUTURE LED 3500LM 850 220-240V IP54 II 5M UNI-SCHUKO GREY (26W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621345
Category type:	general construction site lighting
Light source:	LED module
Nominal power [W]:	26
Luminous flux [lm]:	3500
Supply voltage [V]:	220-240
Luminous efficacy [lm/W]:	158
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	5000
Diffuser material:	PC

Diffuser type:	milky
Material of the body:	PP
Colour of the body:	graphite
Dimensions (H/W/T/S) [mm]:	ø198/154
Impact resistance:	IK10
Ingress protection:	IP54
Plug type:	UNI-SCHUKO
Cable length [m]:	5
Net weight [kg]:	1.400
Manual:	Download PDF

Card creation date: 30 June 2020



