

SITE LITE FUTURE LED 3500LM 850 220-240V IP54 II 5M UNI-SCHUKO GREY (26W) MAGNET

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621369
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	26
Colour temperature [K]:	5000
Luminous flux [lm]*:	3500
Energy efficiency class:	D
Electrical protection class:	II
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets
- with a magnet in the base

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 3500LM 850 220-240V IP54 II 5M UNI-SCHUKO GREY (26W) MAGNET

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621369	Diffuser type:	milky
Category type:	general construction site lighting	Material of the body:	PP
Light source:	LED module	Colour of the body:	graphite
Nominal power [W]:	26	Dimensions (H/W/T/S) [mm]:	ø198/154
Luminous flux [lm]:	3500	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP54
Luminous efficacy [lm/W]:	158	Plug type:	UNI-SCHUKO
Energy efficiency class:	D	Cable length [m]:	5
Electrical protection class:	II	Magnet:	yes
Colour temperature [K]:	5000	Net weight [kg]:	1.400
Diffuser material:	PC	Manual:	Download PDF

Card creation date: 30 June 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 271/2023