

# SITE LITE FUTURE LED 2200LM 840 24-48V IP44 III KL. 5M WT. CEE Z GNIAZDEM CEE SZARY (20W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	621284
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2200
Electrical protection class:	III
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky

## CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# SITE LITE FUTURE LED 2200LM 840 24-48V IP44 III KL. 5M WT. CEE Z GNIAZDEM CEE SZARY (20W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	621284	Colour of the body:	graphite
Category type:	general construction site lighting	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP44
Nominal power [W]:	20	Plug type:	CEE
Luminous flux [lm]:	2200	Socket type:	CEE
Supply voltage [V]:	24-48	Sockets:	1
Electrical protection class:	III	Cable length [m]:	5
Colour temperature [K]:	4000	Net weight [kg]:	1.400
Diffuser material:	PC	Dimensions (H/W/T/S) [mm]:	ø198/154
Diffuser type:	milky	Manual:	<a href="#">Download PDF</a>
Material of the body:	PP		