

SITE LITE FUTURE LED 2200LM 840 24-48V IP54 III KL. 5M WT. CEE SZARY (20W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621277
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2200
Electrical protection class:	III
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 2200LM 840 24-48V IP54 III KL. 5M WT. CEE SZARY (20W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20	Colour of the body:	graphite
Index:	621277	Impact resistance:	IK10
Colour temperature [K]:	4000	Plug type:	CEE
Category type:	general construction site lighting	Ingress protection:	IP54
Luminous flux [lm]:	2200	Cable length [m]:	5
Light source:	LED module	Net weight [kg]:	1.400
Supply voltage [V]:	24-48	Dimensions (H/W/T/S) [mm]:	ø198/154
Electrical protection class:	III	Manual:	Download PDF
Diffuser material:	PC		
Diffuser type:	milky		
Material of the body:	PP		

Card creation date: 01 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 272/2023