

# SITE LITE FUTURE LED 2200LM 840 24-48V IP54/ IP20 III KL. 0,5M B. WT. SZARY (20W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |        |
|-------------------------------------|--------|
| <b>Index:</b>                       | 621260 |
| <b>Ingress protection:</b>          | IP54   |
| <b>Impact resistance:</b>           | IK10   |
| <b>Nominal power [W]:</b>           | 20     |
| <b>Colour temperature [K]:</b>      | 4000   |
| <b>Luminous flux [lm]*:</b>         | 2200   |
| <b>Electrical protection class:</b> | III    |
| <b>Material of the body:</b>        | PP     |
| <b>Diffuser material:</b>           | PC     |
| <b>Diffuser type:</b>               | milky  |

## CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# SITE LITE FUTURE LED 2200LM 840 24-48V IP54/ IP20 III KL. 0,5M B. WT. SZARY (20W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                              |                                    |                            |                              |
|------------------------------|------------------------------------|----------------------------|------------------------------|
| Nominal power [W]:           | 20                                 | Colour of the body:        | graphite                     |
| Index:                       | 621260                             | Impact resistance:         | IK10                         |
| Colour temperature [K]:      | 4000                               | Ingress protection:        | IP54                         |
| Category type:               | general construction site lighting | Cable length [m]:          | 5                            |
| Luminous flux [lm]:          | 2200                               | Net weight [kg]:           | 1.400                        |
| Light source:                | LED module                         | Dimensions (H/W/T/S) [mm]: | ø198/154                     |
| Supply voltage [V]:          | 24-48                              | Manual:                    | <a href="#">Download PDF</a> |
| Electrical protection class: | III                                |                            |                              |
| Diffuser material:           | PC                                 |                            |                              |
| Diffuser type:               | milky                              |                            |                              |
| Material of the body:        | PP                                 |                            |                              |

Card creation date: 01 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 272/2023