SITE LITE FUTURE LED 2200LM 840 24-48V IP54/ IP20 III KL. 0,5M B. WT. SZARY (20W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621260
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2200
Electrical protection class:	III
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 2200LM 840 24-48V IP54/ IP20 III KL. 0,5M B. WT. SZARY (20W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621260
Category type:	general construction site lighting
Light source:	LED module
Nominal power [W]:	20
Luminous flux [lm]:	2200
Supply voltage [V]:	24-48
Electrical protection class:	III
Colour temperature [K]:	4000
Diffuser material:	PC

Diffuser type:	milky
Material of the body:	PP
Colour of the body:	graphite
Impact resistance:	IK10
Ingress protection:	IP54
Cable length [m]:	5
Net weight [kg]:	1.400
Dimensions (H/W/T/S) [mm]:	ø198/154
Manual:	Download PDF

Card creation date: 01 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 272/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl