

SITE LITE FUTURE LED 2200LM 850 24-48V IP54/ IP20 III KL. 0,5M B. WT. SZARY (20W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621406
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	5000
Luminous flux [lm]*:	2200
Electrical protection class:	III
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 2200LM 850 24-48V IP54/ IP20 III KL. 0,5M B. WT. SZARY (20W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621406	Diffuser type:	milky
Category type:	general construction site lighting	Material of the body:	PP
Light source:	LED module	Colour of the body:	graphite
Nominal power [W]:	20	Impact resistance:	IK10
Luminous flux [lm]:	2200	Ingress protection:	IP54
Supply voltage [V]:	24-48	Cable length [m]:	5
Electrical protection class:	III	Net weight [kg]:	1.400
Colour temperature [K]:	5000	Dimensions (H/W/T/S) [mm]:	ø198/154
Diffuser material:	PC	Manual:	Download PDF

Card creation date: 01 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 272/2023