

SITE LITE FUTURE LED 2200LM 850 24-48V IP54/ IP20 III KL. 0,5M B. WT. SZARY (20W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------|--------|
| Index: | 621406 |
| Ingress protection: | IP54 |
| Impact resistance: | IK10 |
| Nominal power [W]: | 20 |
| Colour temperature [K]: | 5000 |
| Luminous flux [lm]*: | 2200 |
| Electrical protection class: | III |
| Material of the body: | PP |
| Diffuser material: | PC |
| Diffuser type: | milky |

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 2200LM 850 24-48V IP54/ IP20 III KL. 0,5M B. WT. SZARY (20W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|------------------------------|------------------------------------|----------------------------|------------------------------|
| Nominal power [W]: | 20 | Colour of the body: | graphite |
| Index: | 621406 | Impact resistance: | IK10 |
| Colour temperature [K]: | 5000 | Ingress protection: | IP54 |
| Category type: | general construction site lighting | Cable length [m]: | 5 |
| Luminous flux [lm]: | 2200 | Net weight [kg]: | 1.400 |
| Light source: | LED module | Dimensions (H/W/T/S) [mm]: | ø198/154 |
| Supply voltage [V]: | 24-48 | Manual: | Download PDF |
| Electrical protection class: | III | | |
| Diffuser material: | PC | | |
| Diffuser type: | milky | | |
| Material of the body: | PP | | |

Card creation date: 01 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 272/2023