

# SITE LITE FUTURE LED BASIC 2600LM 840 230V IP44 I KL. 3M WT. DK Z GNIAZDEM DK SZARY (23W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	621031
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	23
Colour temperature [K]:	4000
Luminous flux [lm]*:	2600
Electrical protection class:	I
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky

## CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets:
- with a magnet in the base

## APPLICATION

The luminaire will provide precise illumination of the workplace. It can be used as a workplace luminaire to illuminate workplaces and construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

# SITE LITE FUTURE LED BASIC 2600LM 840 230V IP44 I KL. 3M WT. DK Z GNIAZDEM DK SZARY (23W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	621031	Ingress protection:	IP44
Category type:	general construction site lighting	Plug type:	DK
Light source:	LED module	Socket type:	DK
Nominal power [W]:	23	Sockets:	1
Luminous flux [lm]:	2600	Cable length [m]:	3
Supply voltage [V]:	220-240	Net weight [kg]:	1.400
Electrical protection class:	I	Dimensions (H/W/T/S) [mm]:	ø198/154
Colour temperature [K]:	4000	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PC	Luminous efficacy [lm/W]:	133
Diffuser type:	milky	Energy efficiency class:	E
Material of the body:	PP	Warranty [years]:	3
Colour of the body:	graphite	CE certificate:	<a href="#">270/2023</a>
Impact resistance:	IK10		

Card creation date: 23 September 2021  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 270/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)