

# SITE LITE FUTURE LED BASIC 2600LM 840 230V IP44 I KL. 3M WT.UNI-SCHUKO Z GNIAZDEM PL-FR SZARY (23W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	621017
<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	23
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	2600
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	PP
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	milky

## CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets:
- with a magnet in the base

## APPLICATION

The luminaire will provide precise illumination of the workplace. It can be used as a workplace luminaire to illuminate workplaces and construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

# SITE LITE FUTURE LED BASIC 2600LM 840 230V IP44 I KL. 3M WT.UNI-SCHUKO Z GNIAZDEM PL-FR SZARY (23W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	23	Impact resistance:	IK10
Index:	621017	Socket type:	PL-FR
Colour temperature [K]:	4000	Ingress protection:	IP54
Category type:	general construction site lighting	Sockets:	1
Luminous flux [lm]:	2600	Cable length [m]:	3
Light source:	LED module	Net weight [kg]:	1.400
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	ø198/154
Electrical protection class:	I	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PC	Luminous efficacy [lm/W]:	133
Diffuser type:	milky	Energy efficiency class:	E
Material of the body:	PP	Warranty [years]:	3
Colour of the body:	graphite	CE certificate:	<a href="#">270/2023</a>
Plug type:	UNI-SCHUKO		

Card creation date: 23 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 270/2023